

# G.J. CHEMICAL COMPANY, INC. SAFETY DATA SHEET

## 1. PRODUCT IDENTIFIER

PRODUCT NAME -----> **Glycol Ether DB**

1.1 PRODUCT NUMBER(S)-----> 169300

TRADE NAMES AND SYNONYMS --> Diethylene Glycol Monobutyl Ether

CAS-No: 112-34-5

CHEMICAL FAMILY: Glycol Ether

### 1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

**RECOMMENDED USE:** Industrial: Use in metal working fluids, Use in mining chemicals, Use as a functional fluid, Use in coatings, inks, and adhesives, Use in cleaning agents, Use in oilfield chemicals, Use in fire foams, Use as an intermediate, Use in lubricants, Use in textile dyeing, Laboratory chemicals.

**USES ADVISED AGAINST:** No information available

### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Company: **G.J. CHEMICAL CO., INC.**

Address: **40 VERONICA AVENUE  
SOMERSET, NJ 08873**

Telephone: **1-973-589-1450**

Fax: **1-973-589-3072**

### 1.4 Emergency Telephone Number

Emergency Phone: **1-800-424-9300 (CHEMTREC)**

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29CFR 1910 (OSHA HCS)

Eye irritation (Category 2A), H319

### 2.1 GHS Label elements, including precautionary statements



Pictogram

GHS07

Signal word: **WARNING**

Hazard statement(s)  
H319 Causes serious eye irritation

Precautionary statement(s)

Prevention:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. INGREDIENTS

3.1 SUBSTANCE:

Ingredient	CAS No.	% by WT. Range	CLASSIFICATION
2-(2-butoxyethoxy)-ethanol EC-No.203-961-6 Index-No. 603-096-00-8 Reg.-No. 1-2119475104-44-XXXX	112-34-5	99	Eye irritation (Category 2A), H319
2-butoxyethanol EC-No.203-905-0 Index-No.603-014-00-0 Reg.-No. 01-2119475108-36-XXXX	111-76-2	0-1	Flammable liquids (Category 4), H227 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332 Acute toxicity, Dermal (Category 4), H312 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319
n-butanol EC-No.200-751-6 Index No.603-004-00-6 Reg.-No. 1-2119484630-38-XXXX	71-36-3	0-02	Flammable liquids (Category 3), H226 Acute toxicity, Oral (Category 4), H302 Skin irritation (Category 2), H315 Serious eye damage (Category 1), H319 STOT-SE (Category 3), Respiratory system, Central nervous system, H335, H336

3.2 MIXTURE: Not applicable

4. FIRST-AID MEASURES

#### 4.1 DESCRIPTION OF FIRST AID MEASURES:

##### **INHALATION: Diethylene Glycol Butyl Ether**

**\*\*FIRST AID- Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep person warm and at rest. Treat symptomatically and supportively. Get medical attention immediately.**

##### **SKIN CONTACT: Diethylene Glycol Butyl Ether**

**\*\*FIRST AID- Remove contaminated clothing and shoes immediately. Wash affected area with waterless cleaner first then soap and large amounts of water until no evidence of chemical remains (approximately 15-20 minutes). Get medical attention immediately.**

##### **EYE CONTACT: Diethylene Glycol Butyl Ether**

**\*\*FIRST AID- Wash eyes immediately with large amounts of water, occasionally lifting upper and lower lids, until no evidence of chemical remains (approximately 15-20 minutes). Remove contact lenses, if worn, after initial flush. Consult a physician if irritation persists.**

##### **INGESTION: Diethylene Glycol Butyl Ether**

**\*\*FIRST AID- Do not induce vomiting. Never give anything by mouth to an unconscious person. Have patient drink several glasses of water. Consult a physician or poison control center, treat symptomatically.**

#### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

**Eye:** Severe to moderate irritation, including tearing, redness and swelling;

**Skin:** Slightly irritating with prolonged contact;

**Inhalation:** May cause irritation to the respiratory tract. Symptoms include coughing, sore throat, labored breathing and chest pain.

**Ingestion:** May cause gastrointestinal tract irritation.

May cause signs of intoxication, such as nausea, headache, in-coordination, dizziness, drowsiness, and slurred speech.

**Chronic:** Repeated inhalation and ingestion can lead to central nervous system, kidney and gastrointestinal disturbances.

**Medical Conditions Aggravated by Exposure:** Any pre-existing disorders of the eye.

#### **4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:**

Specific details on antidote: No recommendation given.

### **5. FIRE FIGHTING MEASURES**

Flash Point: 99°C (210°F) TCC

LEL %:0.9 (V)

Auto-ignition Temp: 210°C (410°F)

UEL %:6.2 (V)

UNIFORM FIRE CODE: Combustible Liquid: III-B

**5.1 SUITABLE EXTINGUISHING MEDIA:** Foam--> x CO2--> x Dry Chemical-->  
x Water-fog--> x Other-->

Unsuitable extinguishing media: Do not use waterjet.

#### **5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR**

**MIXTURE:** Above the Flash Point explosive vapor/air mixtures may be formed.

**CONDITIONS OF FLAMMABILITY:** Flammable in the presence of a source of ignition when the temperature is above the flash point.

**HAZARDOUS COMBUSTION PRODUCTS:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, carbon oxides and other unidentified organic compounds evolve when this material undergoes combustion.

#### **5.3 ADVICE FOR FIREFIGHTERS:**

Shut off source. Keep unnecessary people away; isolate hazard area and deny entry. Avoid breathing vapors, stay upwind Do not spray pool fires directly. A solid stream of water or foam directed into hot burning liquid can cause frothing. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire. Cool containers with flooding amounts of water from as far a distance as possible. Wear NIOSH approved self-contained breathing apparatus for confined

spaces. Use full fire-fighting protective clothing. If protective equipment is not available or not used, fight fire from a protected location or safe distance.

## **6. ACCIDENTAL RELEASE MEASURES**

**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Eliminate ignition sources in the vicinity of the spill or released vapor. Immediately evacuate all nonessential people. Verify that responders are properly trained and wearing appropriate respiratory equipment and fire resistant protective clothing during cleanup operations.

**6.2 ENVIRONMENTAL PRECAUTIONS:**  
Keep out of water sources, drains and sewers. Do not flush into surface water or sanitary sewer system

### **6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:**

Methods for cleanup and containment:

Use explosion proof equipment. Shut off valves, contain spill, keep out of water sources and sewers, for smaller spills add non-flammable absorbent such as clay or silica in spill area. For large spills use foam on spill to minimize vapors clean up by vacuuming then using non-flammable absorbent. Remove contaminated soil to remove contaminated trace residues.

Methods for disposal:

Place all saturated absorbent, using non-sparking tools, in an approved container for disposal. Flush with water to remove trace residue. Minimize breathing vapors and skin contact, ventilate confined areas, open all windows and doors, assure conformity with applicable government regulations.

**6.4 REFERENCE TO OTHER SECTIONS:** See Sections 8 and 13.

## **7. HANDLING AND STORAGE**

**7.1 PRECAUTIONS FOR SAFE HANDLING:** Liquid evaporates and forms vapor (fumes), which can catch fire and burn. Invisible vapor spreads easily and can be set on fire by many sources, such as pilot lights, welding equipment, and electrical motors and switches. Vapor is heavier than air and can travel considerable distance to a source of ignition and flash back. Avoid breathing vapors in top of shipping container. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid breathing vapors in top of shipping container. Avoid work practices that may release volatile components in the atmosphere. Avoid contaminating soil or releasing material into sewage and drainage systems. Use non-sparking tools to open or close containers.

Advice on general occupational hygiene:

Wash hands before breaks and after work. Keep away from food, drink and animal feeding stuffs. When using do not smoke.

**7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**

Follow maximum allowed pile heights specified in the BOCA codes or the NFPA manual. Local fire authorities should be notified for storage of this material in any quantity. Local permits are required for storage in warehouse quantities. Recommended storage temperature: 15 - 25°C. Store large quantities only in buildings designed to comply with OSHA 1910.106. Keep containers tight and upright to prevent leakage. Do not store with incompatible materials. Keep containers closed when not in use.

**CONTAINER WARNINGS:** Containers should be Bonded and Grounded when pouring. Avoid free fall of liquid in excess of a few inches. Empty containers release residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, or expose such containers to heat, sparks, static electricity or other sources of ignition. Do not attempt to clean. "Empty" drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner.

**7.3 SPECIFIC END USES:** Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

**8. EXPOSURE CONTROL (PERSONAL PROTECTION)**

**8.1 CONTROL PARAMETERS:**

Ingredient	CAS No.	% by WT. Range	Exposure Limits
2-(2-butoxyethoxy) - ethanol	112-34-5 EC-No.203-961-6 Index-No. 603-096-00-8 Reg.-No. 1-2119475104-44-XXXX	98-99.5	N.E.
2-butoxyethanol	111-76-2 EC-No.203-905-0 Index-No.603-014-00-0 Reg.-No. 01-2119475108-36-XXXX	0-1	50ppm TWA (OSHA) 20ppm TWA (ACGIH)
n-butanol	71-36-3 EC-No.200-751-6 Index No.603-004-00-6 Reg.-No. 1-2119484630-38-XXXX	0-0.2	100ppm TWA (OSHA)

Key: (PEL) = Permissible Exposure Limit OSHA  
 (TLV) = Threshold Limit Value OSHA & ACGIH  
 (STEL) = Short Term Exposure Limit ACGIH  
 (WEEL) = USA. Workplace Environmental Exposure Levels  
 (TWA) = Time Weighted Average  
 CAS = Chemical Abstracts Registry Number  
 IDLH = Immediate Danger to Life and Health

## 8.2 EXPOSURE CONTROLS

**EXPOSURE GUIDELINES:** Consider the potential hazards of this material (Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended.

**ENGINEERING CONTROLS:** Provide general dilution or local exhaust ventilation in volume and pattern to keep concentrations within permitted exposure limits. All areas should be ventilated in accordance with OSHA Regulation 29 CFR Part 1910. Explosion proof motors should be used in mechanical ventilation.

**RESPIRATORY PROTECTION:** The specific respirator selected must be based on contamination levels found in the work place, must not exceed the working limits of the respirator and be jointly approved by the National Institute for Occupational Safety and Health and the Mine Safety and Health Administration (NIOSH-MSHA):

For vapor concentrations 1 to 10 times OSHA TWA or PEL an air supplied NIOSH/MSHA Approved respirator with full face-piece and organic vapor cartridges. For concentrations over 10 times OSHA TWA or PEL and in confined areas use a approved positive pressure full face-piece supplied air respirator.

### **BODY CLOTHING:**

Employee must wear appropriate protective (impervious) clothing and equipment to prevent repeated or prolonged contact with this substance. Use chemical resistant apron or other impervious clothing. Remove and wash contaminated clothing before reuse.

### **SKIN PROTECTION:**

Employee must wear appropriate protective gloves to prevent contact with this substance.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 49 min

**HYGIENE:** Use good personal hygiene practices, wash hands before eating, drinking, smoking or using toilet facilities.

**EYE/FACE PROTECTION:** Use safety eyewear with splash guards or face shield. Emergency shower and eyewash should be easily accessible to the work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Glycol Ether DB 112-34-5

APPEARANCE:	Clear liquid
COLOR:	Colorless
ODOR:	Mild butyl odor
ODOR THRESHOLD:	No Data Available
pH:	6-7.5
MOLECULAR WEIGHT:	162.23 amu
MELTING POINT:	-68°C (-90°F)
BOILING POINT:	231°C (448°F)
SPECIFIC GRAVITY:	0.95@25°C
DENSITY (25°C):	0.967 g/ml @20°C
VAPOR PRESSURE:	0.02 mm Hg @ 20°C (68.0°F)
VAPOR DENSITY:	5.6
WATER SOLUBILITY:	Complete
PARTITION COEFFICIENT N-OCTANOL/WATER	log Pow: 1 at 20°C (68°F)
FLASH POINT:	99°C (210°F) - closed cup
EVAPORATION RATE (BUTYL ACETATE=1):	>0.01
UPPER FLAMMABILITY LIMIT:	6.2% (V)
LOWER FLAMMABILITY LIMIT:	0.9% (V)
AUTO IGNITION TEMPERATURE:	210°C (410°F)
DECOMPOSITION TEMPERATURE:	No data available
VISCOSITY:	6.122 mm <sup>2</sup> /s at 20°C (68°F)
EXPLOSIVE PROPERTIES:	No data available
OXIDIZING PROPERTIES:	No data available

### 9.2 OTHER INFORMATION:

Surface tension: 32.8 mN/m at 20°C (68°F)

## 10. STABILITY AND REACTIVITY INFORMATION

10.1 REACTIVITY: No data available.

10.2 CHEMICAL STABILITY: Unstable ( ) Stable (X)  
Stable under recommended storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS: No data available

HAZARDOUS POLYMERIZATION: May occur ( ) Will not occur (X)

10.4 CONDITIONS TO AVOID: Heat, Sparks, Pilot Lights, Static Electricity, and Open Flame.

10.5 INCOMPATIBLE MATERIALS: Strong oxidants such as liquid chlorine,



oxygen, sodium hypochlorite, inorganic acids e.g. hydrochloric acid, hydrogen peroxide.

**10.6 HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes, Smoke, Carbon Monoxide, Aldehydes and other decomposition products where combustion is not complete.

## **11. TOXICOLOGICAL INFORMATION**

### **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:**

Routes of Entry: Inhalation--> x Skin--> x Ingestion--> x Eye--> x

#### **ACUTE HEALTH EFFECTS:**

Effects of overexposure:

Eye> Severe to moderate irritation, including tearing, redness and swelling;

Skin> Slightly irritating with prolonged contact;

Inhalation> May cause irritation to the respiratory tract. Symptoms include coughing, sore throat, labored breathing and chest pain.

Ingestion> May cause gastrointestinal tract irritation.

May cause signs of intoxication, such as nausea, headache, in-coordination, dizziness, drowsiness, and slurred speech.

Chronic: Repeated inhalation and ingestion can lead to central nervous system, kidney and gastrointestinal disturbances.

Medical Conditions Aggravated by Exposure> Any pre-existing disorders of the eye.

#### **ACUTE TOXICITY:**

The effects of overexposure shown in Section II are based on acute toxicity profiles. Typical values are:

<b>Ingredient</b>	<b> Oral LD50 (Rat)</b>	<b> Skin LD50 (Rabbit)</b>	<b>  Inhalation LC50  </b>
<b>Glycol Ether DB</b>	<b>5660mg/kg</b>	<b>4120mg/kg</b>	
<b>Glycol Ether EB</b>	<b>2.4g/kg</b>	<b>400mg/kg</b>	<b>500ppm/4hr</b>

**SKIN CORROSION/IRRITATION: Skin - Rabbit Result: Mild skin irritation - 1 h (OECD Test Guideline 404)**

**SERIOUS EYE DAMAGE/EYE IRRITATION: Eyes - Rabbit Result: Irritating to eyes. (OECD Test Guideline 405)**

**RESPIRATORY OR SKIN SENSITIZATION: Maximization Test (GPMT) - Guinea pig Result: Does not cause skin sensitization. (OECD Test Guideline 406)**

**MUTAGENIC EFFECTS: Ames test *S. typhimurium* Result: negative OECD Test Guideline 477 *Drosophila melanogaster* - male and female Result: negative**

**CARCINOGEN STATUS:**

**IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.**

**NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.**

**OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.**

**REPRODUCTIVE TOXICITY: Reproductive toxicity - rat - male and female - Dermal No adverse effect has been observed in chronic toxicity tests.**

**Developmental Toxicity - rabbit - Dermal**

**No adverse effect has been observed in chronic toxicity tests.**

**Specific target organ toxicity (STOT-SE) - single exposure (Globally Harmonized System): no data available**

**Specific target organ toxicity (STOT-RE) - repeated exposure (Globally Harmonized System): no data available**

**ASPIRATION HAZARD: No data available**

**11.2 ADDITIONAL DATA: Stomach - Irregularities - Based on Human Evidence RTECS: KJ9100000**

## **12. ECOLOGICAL INFORMATION**

### **12.1 AQUATIC TOXICITY;**

**Toxicity to Fish:**

**LC50 - *Lepomis macrochirus* - 1,300 mg/l - 96 h**

**LC0 - *Leuciscus idus* (Golden orfe) - > 1,000 mg/l - 48 h**

**Toxicity to daphnia and other aquatic invertebrates:**

**EC50 - *Daphnia magna* (Water flea) - > 100 mg/l - 48 h**

Toxicity to algae IC50 - *Desmodesmus subspicatus* (green algae) - > 100 mg/l - 24h

Toxicity to bacteria LC50 - *Pseudomonas putida* - 1,170 mg/l - 16 h

**12.2 PERSISTENCE AND DEGRADABILITY:** When released to the soil, this material is not expected to evaporate significantly and may leach into groundwater. This product may biodegrade moderately in the soil. When released into the air this material, is expected to be readily degraded by reaction, with photo-chemically produced hydroxyl radicals with a half-life of less than 1 day.

**12.3 BIOACCUMULATIVE POTENTIAL:** This material is highly soluble in water and should not bio-accumulate in aquatic or terrestrial organisms.  
Octanol/Water Partition Coefficient: log Pow: 1  
Biological Oxygen Demand (BOD): No data available  
Bio-concentration Factor (BCF): no data available

**12.4 MOBILITY IN SOIL:** No data available

**12.5 RESULTS OF PBT AND vPvB:**

PBT assessment results: This substance is not classified as PBT or vPvB.

**12.6 OTHER ADVERSE EFFECTS:** This material is highly soluble in water. This material should exhibit low toxicity to aquatic organisms and to rats. The odor and flavor of this material may attract some wildlife and cause them to consume spilled product.

## **13. DISPOSAL CONSIDERATIONS**

**13.1 WASTE TREATMENT METHODS:** Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly it is the responsibility of the user to determine the proper storage, transportation, treatment and or disposal methodologies for spent materials and residues at time of disposition. Dispose in accordance with all applicable disposal regulations.

**CONTAMINATED PACKAGING:** Dispose of as unused product.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

## 14. TRANSPORT INFORMATION

### Land Transport (DOT)

- 14.1 USDOT ID Number-----> N/A
- 14.2 USDOT Shipping Name-----> Not DOT Regulated  
Not Dangerous Goods
- 14.3 USDOT Hazard Classification-----> N/A  
USDOT Label Codes-----> N/A
- 14.4 USDOT Package Code-----> N/A
- 14.5 Marine Pollutant-----> No
- 14.6 Special precautions for user-----> None

### Sea Transport (IMDG)

- 14.1 UN Number:-----> N/A
- 14.2 Proper Shipping Name-----> Not Dangerous Goods
- 14.3 Hazard Class:-----> N/A  
USDOT Label Codes-----> N/A
- 14.4 Packing Group:-----> N/A
- 14.5 Marine Polutant-----> No

### Air Transport (IATA)

- 14.1 UN Number:-----> N/A
- 14.2 Proper Shipping Name:-----> Not Dangerous goods
- 14.3 Hazard Class:-----> N/A  
USDOT Label Codes-----> N/A
- 14.4 Packing Group:-----> N/A
- 14.5 Environmental hazard-----> No

## 15. REGULATORY INFORMATION

### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

#### SARA TITLE III (Superfund Amendment and Reauthorization Act)

SECTION 302 AND 304: Extremely Hazardous Substance List (40 CFR 355) - Not Listed

SECTION 313: Toxic Chemicals Listing (40 CFR 372.65) - Listed - 2- (2-Butoxyethoxy) ethanol CAS-No.112-34-5, 2-Butoxyethanol CAS-No.111-76-2  
n-Butanol CAS-No.71-36-3

**SECTION 311/312: Hazard Categorization (40 CFR 370) - Acute Health Hazard, Chronic Health Hazard**

**CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)**

**SECTION 102(A) Hazardous Substances (40 CFR 302.4) - Listed**

**2-(2-Butoxyethoxy) ethanol CAS-No.112-34-5**

**Reportable Quantity – n-Butanol CAS-No.71-36-3, (0-0.02%) – 5000lbs.**

**SECTION 101(14) Reportable Quantity: n-Butanol CAS-No.71-36-3, (0-0.02%) – 5000lbs.**

**Massachusetts Right to Know Components**

**2-Butoxyethanol CAS-No.111-76-2**

**n-Butanol CAS-No.71-36-3**

**Pennsylvania Right to Know Components**

**2-(2-Butoxyethoxy) ethanol CAS-No.112-34-5**

**2-Butoxyethanol CAS-No.111-76-2**

**n-Butanol CAS-No.71-36-3**

**New Jersey Right to Know Components**

**2-(2-Butoxyethoxy) ethanol CAS-No.112-34-5**

**2-Butoxyethanol CAS-No.111-76-2**

**n-Butanol CAS-No.71-36-3**

**California Prop. 65 Components**

**This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.**

**TSCA (Toxic Substance Control Act)**

**2-(2-Butoxyethoxy) ethanol CAS-No.112-34-5, 2-Butoxyethanol CAS-No.111-76-2, n-Butanol CAS-No.71-36-3 are listed on the TSCA Inventory.**

**International Inventories:**

<b>Country or Region</b>	<b>Inventory Name</b>	<b>On inventory yes/no</b>
<b><u>Australia</u></b>	Australian Inventory of Chemical Substances (AICS)	Yes
<b><u>Canada</u></b>	Domestic Substances List (DSL)	Yes
<b><u>Canada</u></b>	Non-Domestic Substances List (NDSL)	No
<b><u>China</u></b>	Inventory of Existing Chemical Substances in China (IECSC)	Yes
<b><u>Europe</u></b>	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
<b><u>Europe</u></b>	European List of Notified Chemical Substances (ELINCS)	No

<u>Japan</u>	Inventory of Existing and New Chemical Substances (ENCS)	Yes
<u>Japan</u>	Industrial Safety & Health Law Inventory (ISHL)	Yes
<u>Korea</u>	Existing Chemicals List (ECL)	Yes
<u>Mexico</u>	National Inventory of Chemical Substances (INSQ)	Yes
<u>New Zealand</u>	New Zealand Inventory	Yes
<u>Philippines</u>	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
<u>Switzerland</u>	Inventory of Notified New Substances (CHINV)	Yes
<u>Taiwan</u>	National Existing Chemical Inventory (NECI)	Yes
<u>United States &amp; Puerto Rico</u>	Toxic Substances Control Act Inventory	Yes

**15.2 CHEMICAL SAFETY ASSESSMENT: A chemical safety assessment has been carried out for this substance.**

## **16. OTHER INFORMATION:**

**HMIS** (Hazardous Materials Identification System)

**Hazard Rating:**

**4-Extreme**

**3-High**

**2-Moderate**

**1-Slight**

**0-Insignificant**

**NFPA RATINGS (SCALE 0-4): Health=2 Fire=1 Reactivity=0**

**HMIS RATINGS (SCALE 0-4): Health=2 Fire=1Reactivity=0 PPE=G**

**Hazard statement(s) from Section 2 and 3:**

**H319 Causes serious eye irritation**

**Date of preparation-----> October 30, 2002**

**Revision Number-----> 1.7**

**Revision Content-----> Updated Sections: 1, 4, 8, 10, 11, 15, and 16**

**Revision Date-----> February 18, 2019**

**Prepared by-----> T.G. Fenstermaker Jr.**

### **Acronyms:**

ACGIH	-	American Conference of Governmental Industrial Hygienists
AIHA	-	American Industrial Hygiene Association
ANSI	-	American Nation Standards Institute
API	-	American Petroleum Institute
CERCLA	-	Comprehensive Emergency Response, Compensation, and Liability Act
DOT	-	U.S. Department of Transportation
EPA	-	U.S. Environmental Protection Agency
HMIS	-	Hazardous Materials Information System
IARC	-	International Agency For Research On Cancer
MSHA	-	Mine Safety and Health Administration
NFPA	-	National Fire Protection Association
NIOSH	-	National Institute of Occupational Safety and Health
NOIC	-	Notice of Intended Change (Proposed change to ACGIH TLV)
NTP	-	National Toxicology Program
OPA	-	Oil Pollution Act of 1990

OSHA	-	U.S. Occupational Safety & Health Administration
PEL	-	Permissible Exposure Limit (OSHA)
RCRA	-	Resource Conservation and Recovery Act
REL	-	Recommended Exposure Limit (NIOSH)
SARA	-	Superfund Amendments and Reauthorization Act of 1986 Title III
SCBA	-	Self-Contained Breathing Apparatus
STEL	-	Short-Term Exposure Limit (generally 15 minutes)
TLV	-	Threshold Limit Value
TSCA	-	Toxic Substances Control Act
TWA	-	Time Weighted Average (8hr.)
WHMIS	-	Canadian Workplace Hazardous Materials Information System

This information is furnished without warranty, representation, inducement of license of any kind, except that it is accurate to the best of G.J. Chemical's knowledge, or obtained from sources believed by G.J. Chemical Co., Inc. to be accurate, and G.J. Chemical Co., Inc. does not assume any legal responsibility for use or reliance upon same. Users are encouraged to conduct their own tests. Before using any product, read its label. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.