

G.J. CHEMICAL COMPANY, INC. SAFETY DATA SHEET

1. PRODUCT IDENTIFIER

1.1 PRODUCT NAME -----> **GLYCOL ETHER PNP**

PRODUCT NUMBER(S) -----> 173500

TRADE NAMES/SYNONYMS -----> 1-Propoxy-2-propanol
Propylene Glycol Monopropyl Ether

CAS-No: 1569-01-3 Chemical Family: Glycol Ether

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

RECOMMENDED USE: Industrial: Use in coatings, Use in cleaning agents, Use as a process solvent, Distribution, Laboratory chemicals.

USES ADVISED AGAINST: No information available

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Company: **G.J. CHEMICAL CO., INC.**

Address: **40 VERONICA AVENUE
SOMERSET, NJ 08873**

Telephone: **1-973-589-1450**

Fax: **1-973-589-3072**

1.4 Emergency Telephone Number

Emergency Phone: **1-800-424-9300 (CHEMTREC)**

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Eye irritation (Category 2A), H319

2.2 GHS Label elements, including precautionary statements

Pictogram



GHS02 GHS07
Signal word: WARNING

Hazard statement(s)

H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.

Precautionary statement(s)

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plan

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. INGREDIENTS

3.1 SUBSTANCE:

Ingredient	CAS No.	% by WT. Range	CLASSIFICATION
1-Propoxy-2-Propanol EC-No.216-372-4 Reg.-No. 01-2119474443-37-XXXX	1569-01-3	>99	Flammable liquids (Category 3), H226 Eye irritation (Category 2A), H319

3.2 MIXTURE: Not applicable

4. FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

INHALATION: Propylene Glycol Monopropyl Ether

****FIRST AID-** Remove from exposure area to fresh air immediately. If breathing has stopped, give oxygen and/or perform artificial respiration. Keep person warm and at rest. Treat symptomatically and supportively. Get medical attention immediately.

SKIN CONTACT: Propylene Glycol Monopropyl Ether

****FIRST AID-** Remove contaminated clothing and shoes immediately. Wash affected area with soap or mild detergent and large amounts of water until no evidence of chemical remains (approximately 15-20 minutes). Get medical attention immediately.

EYE CONTACT: Propylene Glycol Monopropyl Ether

****FIRST AID-** Wash eyes immediately with large amounts of water or normal saline, occasionally lifting upper and lower lids, until no evidence of chemical remains (approximately 15-20 minutes). Remove contact lenses, if worn, after initial flush. Get medical attention immediately.

INGESTION: Propylene Glycol Monopropyl Ether

****FIRST AID-** Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Small amounts, which enter the mouth should be rinsed out until taste is gone. Get medical attention immediately.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Eye: May cause eye irritation; burning and redness.

Skin: May cause skin irritation.

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation; May cause drowsiness and dizziness.

Ingestion: May be harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May damage kidneys.

Chronic:

Inhalation: No information found.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Specific details on antidote: No recommendation given.

5. FIRE FIGHTING MEASURES

Flash Point: 48°C (118.4°F) TCC

LEL %:1.3 (V)

Auto-ignition Temp : 252°C (486°F)

UEL %:10.6 (V)

UNIFORM FIRE CODE: Combustible Liquid Class II

5.1 SUITABLE EXTINGUISHING MEDIA: Foam--> x CO2--> x Dry Chemical-->
x Water-fog--> x Other-->

Unsuitable extinguishing media: Do not use waterjet.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: DANGEROUS FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE ALONG THE GROUND TO A SOURCE OF IGNITION AND FLASH BACK. Keep containers tightly closed. Combustible liquid; isolate from all sources of ignition. Closed containers may explode when exposed to extreme heat. Releases vapors at ambient temperatures. Fine sprays/mists may be combustible at temperature below flash point.

CONDITIONS OF FLAMMABILITY: Flammable in the presence of a source of ignition when the temperature is above the flash point.

HAZARDOUS COMBUSTION PRODUCTS: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, carbon oxides and other unidentified organic compounds evolve when this material undergoes combustion.

5.3 ADVICE FOR FIREFIGHTERS: Shut off source. Keep unnecessary people away; isolate hazard area and deny entry. Avoid breathing vapors, stay upwind Do not spray pool fires directly. A solid stream of water or foam directed into hot burning liquid can cause frothing. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles; if this is impossible, withdraw from area and let

fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire. Cool containers with water fog as far as possible. Wear NIOSH/MSHA approved self-contained breathing apparatus (SCBA) for confined spaces. Use full fire-fighting protective clothing. If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Combustible Liquid; Eliminate ignition sources in the vicinity of the spill or released vapor. Immediately evacuate all nonessential people. Verify that responders are properly trained and wearing appropriate respiratory equipment and fire resistant protective clothing during cleanup operations. For large spills evacuate downwind areas as conditions warrant to prevent exposure and to allow vapors or fumes to dissipate.

6.2 ENVIRONMENTAL PRECAUTIONS:

Keep out of water sources, drains and sewers. Do not flush into surface water or sanitary sewer system

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Methods for cleanup and containment:

Use explosion proof equipment. Shut off valves, contain spill, keep out of water sources and sewers, for smaller spills add non-flammable absorbent in spill area. For large spills use foam on spill to minimize vapors clean up by vacuuming then using non-flammable absorbent.

Methods for disposal:

Place all saturated absorbent, using non-sparking tools, in an approved container for disposal. Minimize breathing vapors and skin contact, ventilate confined areas, open all windows and doors, assure conformity with applicable government regulations.

6.4 REFERENCE TO OTHER SECTIONS: See Sections 8 and 13.

7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING: This material presents a fire hazard. Liquid quickly evaporates and forms vapor (fumes), which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources, such as pilot lights, welding equipment, and electrical motors and switches. Vapor is heavier than air and can travel considerable distance to a source of ignition and flash back. Avoid breathing vapors in top of shipping container. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid work practices that may release volatile components in the atmosphere. Avoid contaminating soil or releasing material into sewage and drainage systems. Use non-sparking tools to open or close containers.

Advice on general occupational hygiene:

Wash hands before breaks and after work. Keep away from food, drink and animal feeding stuffs. When using do not smoke.

STATIC HAZARD: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not be sufficient. For more information refer to OSHA Standard 29CFR 1910.106 “Flammable and Combustible Liquids” and National Fire Protection Association (NFPA 77) “Recommended Practice on Static Electricity”.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Follow maximum allowed pile heights specified in the BOCA codes or the NFPA manual. Local fire authorities should be notified for storage of this material in any quantity. Local permits are required for storage in warehouse quantities. Recommended storage temperature: 15 - 25°C. Store large quantities only in cool, dry areas in buildings designed to comply with OSHA 1910.106. Keep containers tight and upright to prevent leakage. Do not contact with oxidizing materials. Keep containers closed when not in use. Storage class (TRGS 510): Flammable liquids

CONTAINER WARNINGS: Containers should be Bonded and Grounded when pouring. Avoid free fall of liquid in excess of a few inches. Empty containers release residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, or expose such containers to heat, sparks, static electricity or other sources of ignition. Do not attempt to clean.

"Empty" drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner.

7.3 SPECIFIC END USES: Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROL (PERSONAL PROTECTION)

8.1 CONTROL PARAMETERS:

Ingredient	CAS No.	% by WT. Range	Exposure Limits
1-Propoxy-2-Propanol	1569-01-3	>99	N.E.
	EC-No.216-372-4		
	Reg.-No. 01-2119474443-37-XXXX		

Key: (PEL) = Permissible Exposure Limit OSHA
(TLV) = Threshold Limit Value OSHA & ACGIH
(STEL) = Short Term Exposure Limit ACGIH
(WEEL) = USA. Workplace Environmental Exposure Levels

(TWA) = Time Weighted Average
CAS = Chemical Abstracts Registry Number
IDLH = Immediate Danger to Life and Health
N.E. =None Established

8.2 EXPOSURE CONTROLS

EXPOSURE GUIDELINES: Consider the potential hazards of this material (Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended.

ENGINEERING CONTROLS: Provide general dilution or local exhaust ventilation in volume and pattern to keep concentrations within permitted exposure limits. All areas should be ventilated in accordance with OSHA Regulation 29 CFR Part 1910. Explosion proof motors should be used in mechanical ventilation.

RESPIRATORY PROTECTION: The specific respirator selected must be based on contamination levels found in the work place, must not exceed the working limits of the respirator and be jointly approved by the National Institute for Occupational Safety and Health and the Mine Safety and Health Administration (NIOSH-MSHA):

For vapor concentrations, an air purifying NIOSH/MSHA Approved respirator with full face-piece and organic vapor cartridges. For emergencies and concentrations in confined areas use a NIOSH approved positive pressure full face-piece supplied air respirator (SCBA).

BODY CLOTHING: Employee must wear appropriate protective (impervious) clothing and equipment to prevent repeated or prolonged contact with this substance. Use chemical resistant apron or other impervious clothing. Remove and wash contaminated clothing before reuse.

SKIN PROTECTION: Employee must wear appropriate protective gloves to prevent contact with this substance.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 30 min

HYGIENE: Use good personal hygiene practices, wash hands before eating, drinking, smoking or using toilet facilities.

EYE/FACE PROTECTION: Use safety eyewear with splash-guards or face shield. Emergency shower and eyewash should be easily accessible to the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Glycol Ether PNP (Propylene Glycol Monopropyl Ether) 1569-01-3

APPEARANCE:	Clear liquid
COLOR:	Colorless
ODOR:	Ether-like odor
ODOR THRESHOLD:	No data Available
pH:	No data available
MOLECULAR WEIGHT:	118.17 amu
MELTING POINT:	-70°C (-94°F)
BOILING POINT:	140 - 160°C (284 - 320°F)
SPECIFIC GRAVITY:	0.887@ 20°C (68°F)
DENSITY (25°C):	0.885 g/ml @ 25°C (77°F)
VAPOR PRESSURE:	2.85 mmHg @ 25°C (77°F)
VAPOR DENSITY:	No data available
WATER SOLUBILITY:	No data available
PARTITION COEFFICIENT N-OCTANOL/WATER	No data available
FLASH POINT:	48°C (118.4°F) - closed cup
EVAPORATION RATE (BUTYL ACETATE=1):	No data available
UPPER FLAMMABILITY LIMIT:	10.6% (V)
LOWER FLAMMABILITY LIMIT:	1.3% (V)
AUTO IGNITION TEMPERATURE:	252°C (486°F)
DECOMPOSITION TEMPERATURE:	No data available
VISCOSITY:	No data available
EXPLOSIVE PROPERTIES:	No data available
OXIDIZING PROPERTIES:	No data available

9.2 OTHER INFORMATION: No data available

10. STABILITY AND REACTIVITY INFORMATION

10.1 REACTIVITY: No data available.

10.2 CHEMICAL STABILITY: Unstable () Stable (X)

10.3 POSSIBILITY OF HAZARDOUS REACTIONS: No data available

HAZARDOUS POLYMERIZATION: May occur () Will not occur (X)

10.4 CONDITIONS TO AVOID: Heat, Sparks, Pilot Lights, Static Electricity, Open Flame and oxidizing conditions.

10.5 INCOMPATIBLE MATERIALS: Strong oxidants such as liquid chlorine, sodium hypochlorite, inorganic acids e.g. hydrochloric acid hydrogen

peroxide.

10.6 **HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes, Smoke, Carbon Monoxide, Carbon Dioxide and other decomposition products where combustion is not complete.

11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

Routes of Entry: Inhalation--> x Skin--> x Ingestion--> x Eye--> x

ACUTE HEALTH EFFECTS:

Effects of overexposure:

Eye> May cause eye irritation; burning and redness.

Skin> May cause skin irritation.

Inhalation> May be harmful if inhaled. Causes respiratory tract irritation; May cause drowsiness and dizziness.

Ingestion> May be harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May damage kidneys.

Chronic:

Inhalation: No information found.

ACUTE TOXICITY;

The effects of overexposure shown in Section II are based on acute toxicity profiles. Typical values are:

Ingredient	Oral LD50 (Rat)	Skin LD50 (Rabbit)	Inhalation LC50
1-Propoxy-2-Propanol	2490mg/kg	4330mg/kg	N.D.

SKIN CORROSION/IRRITATION: Skin - Rabbit Result: No skin irritation - 4 h (OECD Test Guideline 404)

SERIOUS EYE DAMAGE/EYE IRRITATION: Eyes - Rabbit Result: Irritating to eyes.

(OECD Test Guideline 405)

RESPIRATORY OR SKIN SENSITIZATION: - Mouse Result: Does not cause skin sensitization. (OECD Test Guideline 429)

MUTAGENIC EFFECTS: Hamster ovary Result: negative

CARCINOGEN STATUS:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

REPRODUCTIVE TOXICITY: No data available

Specific target organ toxicity (STOT-SE) - single exposure (Globally Harmonized System): Inhalation – no data available

Specific target organ toxicity (STOT-RE) - repeated exposure (Globally Harmonized System): no data available

ASPIRATION HAZARD: No data available

11.2 ADDITIONAL DATA: No data available.

RTECS: UB9351000

12. ECOLOGICAL INFORMATION

12.1 AQUATIC TOXICITY:

Toxicity to fish:

LC50 - Oncorhynchus mykiss (rainbow trout) - > 100 mg/l - 96 h Static Test

Toxicity to daphnia and other aquatic invertebrates:

LC50 - Daphnia magna (Water flea) - > 100 mg/l - 48 h Static Test

Toxicity to algae:

EC50 - Pseudokirchneriella subcapitata - 3,440 mg/l - 72 h Static Test

12.2 PERSISTENCE AND DEGRADABILITY:

aerobic - Exposure time 28 d Result: 91.5 % - Readily biodegradable (OECD Test Guideline 301A)

BIOLOGICAL Oxygen Demand (BOD): No data available

12.3 BIOACCUMULATIVE POTENTIAL: No data available

Bio-concentration Factor (BCF): no data available

12.4 MOBILITY IN SOIL:

12.5 RESULTS OF PBT AND vPvB:

PBT assessment results: This substance is not classified as PBT or vPvB.

12.6 OTHER ADVERSE EFFECTS: No data available.

13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS: Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly it is the responsibility of the user to determine the proper storage, transportation, treatment and or disposal methodologies for spent materials and residues at time of disposition. Incinerate under controlled conditions in a permitted facility.

Dispose in accordance with all applicable disposal regulations. Dilute aqueous waste may biodegrade. Avoid overloading/poisoning plant biomass.

CONTAMINATED PACKAGING: Dispose of as unused product.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

Land Transport (DOT)

14.1 USDOT ID Number-----> UN3271

14.2 USDOT Shipping Name-----> Ethers, n.o.s. (1-Propoxy-2-Propanol)

14.3 USDOT Hazard Classification-----> 3 (Flammable Liquid)

USDOT Label Codes-----> 3

14.4 USDOT Package Code-----> III

14.5 Marine Pollutant-----> No

14.6 Special precautions for user-----> No

Emergency Response Guide-----> 127

Sea Transport (IMDG)

14.1 ID Number-----> UN3271

14.2 Proper shipping name-----> ETHERS, N.O.S. (1-PROPOXY-2-PROPANOL)

14.3 Hazard Classification-----> 3 (Flammable Liquid)

Label Codes-----> 3

14.4 Package Code-----> III

14.5 Marine Pollutant-----> No

14.6 Special precautions for user-----> N/A

EMS-Number-----> F-E, S-D

Air Transport (IATA)

- 14.1 ID Number-----> UN3271
- 14.2 Proper shipping name-----> Ethers, n.o.s. (1-Propoxy-2-Propanol)
- 14.3 Hazard Classification-----> 3 (Flammable Liquid)
Label Codes-----> 3
- 14.4 Package Code-----> III
- 14.5 Environmental hazard-----> None
- 14.6 Special precautions for user-----> None

15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

SARA TITLE III (Superfund Amendment and Reauthorization Act)

- SECTION 302 AND 304: Extremely Hazardous Substance List (40 CFR 355) - Not Listed**
- SECTION 313: Toxic Chemicals Listing (40 CFR 372.65) - Not Listed**
- SECTION 311/312: Hazard Categorization (40 CFR 370) - Acute Health Hazard, Fire Hazard**

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

- SECTION 102(A) Hazardous Substances (40 CFR 302.4) - Not Listed**
- Reportable Quantity – None**
- SECTION 101(14) Reportable Quantity: None**

Massachusetts Right to Know Components
No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right to Know Components
Propylene glycol Monopropyl ether CAS-No.1569-01-3

New Jersey Right to Know Components
Propylene glycol Monopropyl ether CAS-No.1569-01-3

California Prop. 65 Components
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

TSCA (Toxic Substance Control Act)
Propylene glycol Monopropyl ether CAS-No.1569-01-3 is listed on the TSCA Inventory.

International Inventories:

<u>Country or Region</u>	<u>Inventory Name</u>	<u>On inventory yes/no</u>
<u>Australia</u>	Australian Inventory of Chemical Substances (AICS)	Yes
<u>Canada</u>	Domestic Substances List (DSL)	Yes

<u>Canada</u>	Non-Domestic Substances List (NDSL)	No
<u>China</u>	Inventory of Existing Chemical Substances in China (IECSC)	Yes
<u>Europe</u>	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
<u>Europe</u>	European List of Notified Chemical Substances (ELINCS)	No
<u>Japan</u>	Inventory of Existing and New Chemical Substances (ENCS)	Yes
<u>Japan</u>	Industrial Safety & Health Law Inventory (ISHL)	Yes
<u>Korea</u>	Existing Chemicals List (ECL)	Yes
<u>Mexico</u>	National Inventory of Chemical Substances (INSQ)	Yes
<u>New Zealand</u>	New Zealand Inventory	Yes
<u>Philippines</u>	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
<u>Switzerland</u>	Inventory of Notified New Substances (CHINV)	Yes
<u>Taiwan</u>	National Existing Chemical Inventory (NECI)	Yes
<u>United States & Puerto Rico</u>	Toxic Substances Control Act Inventory	Yes

15.2 CHEMICAL SAFETY ASSESSMENT: A chemical safety assessment has been carried out for this substance.

16. OTHER INFORMATION:

HMIS (Hazardous Materials Identification System)

Hazard Rating:

4-Extreme

3-High

2-Moderate

1-Slight

0-Insignificant

NFPA RATINGS (SCALE 0-4): Health=2 Fire=2 Reactivity=0
HMIS RATINGS (SCALE 0-4): Health=2 Fire=2 Reactivity=0 PPE=B

Hazard statement(s) from Section 2 and 3:

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

Date of preparation-----> August 13, 2013

Revision Number-----> 1.2

Revision Content-----> Updated Sections: 1, 4, 7, 8, 10, 11, and 16.

Revision Date-----> May 07, 2019

Prepared by-----> T.G. Fenstermaker Jr.

Acronyms:

ACGIH	-	American Conference of Governmental Industrial Hygienists
AIHA	-	American Industrial Hygiene Association
ANSI	-	American National Standards Institute
API	-	American Petroleum Institute
CERCLA	-	Comprehensive Emergency Response, Compensation, and Liability Act
DOT	-	U.S. Department of Transportation
EPA	-	U.S. Environmental Protection Agency
HMIS	-	Hazardous Materials Information System

IARC	-	International Agency For Research On Cancer
MSHA	-	Mine Safety and Health Administration
NFPA	-	National Fire Protection Association
NIOSH	-	National Institute of Occupational Safety and Health
NOIC	-	Notice of Intended Change (Proposed change to ACGIH TLV)
NTP	-	National Toxicology Program
OPA	-	Oil Pollution Act of 1990
OSHA	-	U.S. Occupational Safety & Health Administration
PEL	-	Permissible Exposure Limit (OSHA)
RCRA	-	Resource Conservation and Recovery Act
REL	-	Recommended Exposure Limit (NIOSH)
SARA	-	Superfund Amendments and Reauthorization Act of 1986 Title III
SCBA	-	Self-Contained Breathing Apparatus
STEL	-	Short-Term Exposure Limit (generally 15 minutes)
TLV	-	Threshold Limit Value
TSCA	-	Toxic Substances Control Act
TWA	-	Time Weighted Average (8hr.)
WHMIS	-	Canadian Workplace Hazardous Materials Information System

This information is furnished without warranty, representation, inducement of license of any kind, except that it is accurate to the best of G.J. Chemical's knowledge, or obtained from sources believed by G.J. Chemical Co., Inc. to be accurate, and G.J. Chemical Co., Inc. does not assume any legal responsibility for use or reliance upon same. Users are encouraged to conduct their own tests. Before using any product, read its label. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.