

# G.J. CHEMICAL COMPANY, INC. SAFETY DATA SHEET

## 1. PRODUCT IDENTIFIER

1.1 PRODUCT NAME:-----> **ISOBUTANOL All Grades**

PRODUCT NUMBER(S):-----> 180700, 180800

TRADE NAMES/SYNONYMS:----> Isobutyl Alcohol, Isopropyl Carbinol  
2-Methyl Propanol

CAS-No: 78-83-1

CHEMICAL FAMILY: Alcohols

### 1.2 RELAVENT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

RECOMMENDED USE: Industrial: Cleaning agents; Coatings; Lubricants; Solvent; intermediate.

USES ADVISED AGAINST: No information available

### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Company: **G.J. CHEMICAL CO., INC.**

Address: 40 VERONICA AVENUE  
SOMERSET, NJ 08873

Telephone: 1-973-589-1450

Fax: 1-973-589-3072

### 1.4 Emergency Telephone Number

Emergency Phone: 1-800-424-9300 (CHEMTREC)

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29CFR 1910

Flammable liquids (Category 3), H226

Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Respiratory system, Central nervous system, H335, H336

GHS Label elements, including precautionary statements



Pictogram

GHS02

GHS05

GHS07

Signal word: **DANGER**

**Hazard statement(s)**

- H226 Flammable liquid and vapor.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

**Precautionary statement(s)**

**Prevention:**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
- P264 Wash skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

- P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340+ P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
- P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**Disposal:**

- P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### 3. INGREDIENTS

#### 3.1 SUBSTANCE:

Ingredient	CAS No.	% by WT.	CLASSIFICATION
------------	---------	----------	----------------

## Range

---

Isobutyl Alcohol	78-83-1	99	Flammable liquids (Category 3), H226
	EC No.201-148-0		Skin irritation (Category 2), H315
	Index No. 603-108-00-1		Serious eye damage (Category 1), H318
Reg.-No. 01-2119484609-23-XXXX			STOT-SE (Category 3), Respiratory system, Central nervous system, H335, H336

---

3.2 MIXTURE: Not applicable.

## 4. FIRST-AID MEASURES

### 4.1 DESCRIPTION OF FIRST AID MEASURES

**INHALATION: Isobutyl Alcohol**

**\*\*FIRST AID- Remove from exposure to fresh air, restore breathing use oxygen if needed. Keep warm and quiet. Immediately notify a physician.**

**EYE CONTACT (Splash): Isobutyl Alcohol**

**\*\*FIRST AID- Immediately flush eyes with water for 15 minutes. Hold eyelids open for complete irrigation. Remove contact lenses, if worn, after initial flush. Immediately take to a physician.**

**SKIN CONTACT (Splash): Isobutyl Alcohol**

**\*\*FIRST AID- Wash affected area with soap and large amounts of water. Remove contaminated clothing and shoes. Consult a physician if irritation persists.**

**INGESTION: Isobutyl Alcohol**

**\*\*FIRST AID- Do NOT induce vomiting of conscious patient. Patient should be made to drink large amounts of water. Never give anything by mouth to an unconscious person. Consult a physician or poison control center, treat symptomatically.**

### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

**Eye:** May cause severe eye irritation;

**Skin:** Mildly irritating;

**Inhalation:** Irritation of the respiratory tract, Coughing, shortness of breath, dizziness and intoxication.

**Ingestion:** Essentially non-toxic. Causes mouth and throat irritation. Can cause nausea, dizziness, headache, and stupor.

**Chronic:** Repeated or prolonged exposure may irritate the mucous membranes in respiratory tract.

**Medical Conditions Aggravated by Exposure:** Skin contact may aggravate an existing dermatitis. May aggravate mucous membrane dysfunction. May adversely affect people with chronic eye conditions.

**4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:** No data available.

## **5. FIRE FIGHTING MEASURES**

Flash Point: 28°C (82°F) TCC                      LEL %:1.7 (V)  
Auto-ignition temperature: 427°C (801°F)      UEL %:10.6 (V)  
UNIFORM FIRE CODE: Flammable Liquid Class 1C

**5.1 SUITABLE EXTINGUISHING MEDIA:** Foam--> x CO2--> x Dry Chemical--> x Water-fog--> x Other-->

Unsuitable extinguishing media: Do not use waterjet.

**5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:** FIRE AND EXPLOSION HAZARD: DANGEROUS FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. VAPOR-AIR MIXTURES ARE EXPLOSIVE Material creates a special hazard because it floats on water. Keep containers tightly closed. Flammable liquid; isolate from all sources of ignition. Closed containers may explode when exposed to extreme heat.

**CONDITIONS OF FLAMMABILITY:** Flammable in the presence of a source of ignition when the temperature is above the flash point.

**HAZARDOUS COMBUSTION PRODUCTS:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, carbon oxides and other unidentified organic compounds evolve when this material undergoes combustion.

**5.3 ADVICE FOR FIREFIGHTERS:** Shut off source. Keep unnecessary people away; isolate hazard area and deny entry. Avoid breathing vapors, stay upwind Do not spray pool fires directly. A solid stream of water or foam directed into hot burning liquid can cause frothing. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire. Water fog may be used to cool closed containers to prevent pressure build up and possible auto ignition or explosion when exposed to extreme heat. Cool containers with water-fog from as far a distance as possible. Wear NIOSH approved self-contained breathing apparatus for confined spaces. Use full fire-fighting protective clothing.

If protective equipment is not available or not used, fight fire from a protected location or safe distance.

## **6. ACCIDENTAL RELEASE MEASURES**

**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Flammable Liquid; Eliminate ignition sources in the vicinity of the spill or released vapor. Immediately evacuate all nonessential people. Verify that responders are properly trained and wearing appropriate respiratory equipment and fire resistant protective clothing during cleanup operations. For large spills evacuate downwind areas as conditions warrant to prevent exposure and to allow vapors or fumes to dissipate.

### **6.2 ENVIRONMENTAL PRECAUTIONS:**

Keep out of water sources and sewers. Do not flush into surface water or sanitary sewer system.

### **6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:**

Methods for cleanup and containment:

Use explosion proof equipment. Shut off valves, contain spill, keep out of water sources and sewers, for smaller spills add non-flammable absorbent in spill area.

For large spills use foam on spill to minimize vapors clean up by vacuuming then using non-flammable absorbent.

Methods for disposal:

Place all saturated absorbent, using non-sparking tools, in an approved container for disposal. Minimize breathing vapors and skin contact, ventilate confined areas, open all windows and doors, assure conformity with applicable government regulations.

### **REPORTABLE QUANTITY (RQ): 5000 POUNDS**

The Superfund Amendments and Reauthorization Act (SARA) Section 304 requires that a release equal to or greater than the reportable quantity for this substance be immediately reported to the local emergency planning committee and the state emergency response commission (40 CFR 355.40). If the release of this substance is reportable under CERCLA Section 103, the national response center must be notified immediately at (800) 424-8882 or (202) 426-2675 in the metropolitan Washington, D. C. area (40 CFR 302.6).

**6.4 REFERENCE TO OTHER SECTIONS:** See Sections 8 and 13.

## **7. HANDLING AND STORAGE**

**7.1 PRECAUTIONS FOR SAFE HANDLING:** This material presents a fire hazard. Liquid quickly evaporates and forms vapor (fumes), which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources, such as pilot lights, welding equipment, and electrical motors and switches. Vapor is heavier than air and can travel considerable distance to a source of ignition and flash back. Avoid breathing vapors in top of shipping container. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid work practices that may release volatile components in the

atmosphere. Avoid contaminating soil or releasing material into sewage and drainage systems. Use non-sparking tools to open or close containers.

Advice on general occupational hygiene:

Wash hands before breaks and after work. Keep away from food, drink and animal feeding stuffs. When using do not smoke.

**STATIC HAZARD:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not be sufficient. For more information refer to OSHA Standard 29CFR 1910.106  Flammable and Combustible Liquids  and National Fire Protection Association (NFPA 77)  Recommended Practice on Static Electricity .

### **7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**

Follow maximum allowed pile heights specified in the BOCA codes or the NFPA manual. Local fire authorities should be notified for storage of this material in any quantity. Local permits are required for storage in warehouse quantities. Recommended storage temperature: 15 - 25 °C. Store large quantities only in cool, dry areas in buildings designed to comply with OSHA 1910.106. Keep containers tight and upright to prevent leakage. Do not contact with oxidizing materials. Keep containers closed when not in use. Do not take internally.

**CONTAINER WARNINGS:** Containers should be Bonded and Grounded when pouring. Avoid free fall of liquid in excess of a few inches. Empty containers release residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, or expose such containers to heat, sparks, static electricity or other sources of ignition. Do not attempt to clean. "Empty" drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner.

**7.3 SPECIFIC END USES:** Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

## **8. EXPOSURE CONTROL (PERSONAL PROTECTION)**

### **8.1 CONTROL PARAMETERS:**

<b>Ingredient</b>	<b>CAS No.</b>	<b>% by WT. Range</b>	<b>Exposure Limits</b>
Isobutyl Alcohol	78-83-1 EC No.201-148-0 Index No. 603-108-00-1 Reg.-No. 01-2119484609-23-XXXX	99	50ppm TWA (NIOSH) 50ppm TWA (ACGIH) 100ppm TWA (OSHA) 1600ppm (IDLH)

Key: (PEL) = Permissible Exposure Limit OSHA

(TLV) = Threshold Limit Value OSHA & ACGIH  
(STEL) = Short Term Exposure Limit ACGIH  
(WEEL) = USA. Workplace Environmental Exposure Levels  
(TWA) = Time Weighted Average  
CAS = Chemical Abstracts Registry Number  
IDLH = Immediate Danger to Life and Health  
N.E. =None Established

## 8.2 EXPOSURE CONTROLS

**EXPOSURE GUIDELINES:** Consider the potential hazards of this material (Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended.

**ENGINEERING CONTROLS:** Provide general dilution or local exhaust ventilation in volume and pattern to keep concentrations within permitted exposure limits. All areas should be ventilated in accordance with OSHA Regulation 29 CFR Part 1910. Explosion proof motors should be used in mechanical ventilation.

**RESPIRATORY PROTECTION:** The specific respirator selected must be based on contamination levels found in the work place, must not exceed the working limits of the respirator and be jointly approved by the National Institute for Occupational Safety and Health and the Mine Safety and Health Administration (NIOSH-MSHA):

For vapor concentrations 1 to 10 times OSHA TLV or PEL an air purifying NIOSH/MSHA Approved respirator with full face-piece and organic vapor cartridges. For concentrations over 10 times OSHA TLV or PEL, in confined areas, and/or where vapor concentrations are unknown use an approved positive pressure full face-piece supplied air respirator.

**BODY CLOTHING:** Employee must wear appropriate protective (impervious) clothing and equipment to prevent repeated or prolonged contact with this substance. Use chemical resistant apron or other impervious clothing. Remove and wash contaminated clothing before reuse.

**SKIN PROTECTION:** Employee must wear appropriate protective gloves to prevent contact with this substance.

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 30 min

**HYGIENE:** Use good personal hygiene practices, wash hands before eating, drinking, smoking or using toilet facilities.

**EYE/FACE PROTECTION:** Use safety eyewear with splash-guards or face shield. Contact lenses should not be worn.

Emergency shower and eyewash should be easily accessible to the work area.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

### **9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:**

#### **Isobutyl Alcohol 78-83-1**

Appearance----->	Clear mobile liquid
Color----->	Colorless
Odor----->	Mild alcohol odor
Odor Threshold----->	No data available
pH----->	No data available
Molecular Weight----->	74.12amu
Melting/Freezing Point----->	-108°C (-162°F)
Boiling Range ----->	108°C (226°F)
Specific Gravity----->	0.803 @20°C (68°F)
Vapor Pressure----->	6 mmHg@20°C (68°F)
Vapor Density (air=1)----->	2.55
Water Solubility----->	70g/L @ 20°C (68°F) – completely miscible
Partition Coefficient n-Octanol/Water->	log Pow 1.0 25°C (77°F)
Evaporation Rate (Butyl Acetate=1)---->	0.82
Flash Point----->	28°C (82°F) - closed cup
Upper Flammability Limit----->	10.6% (V)
Lower Flammability Limit----->	1.7% (V)
Auto-Ignition Temperature----->	427°C (801°F)
Decomposition Temperature----->	No data available
Viscosity----->	No data available
Explosive Properties----->	No data available
Oxidizing Properties----->	No data available

### **9.2 Other Information:**

Surface tension-----> 69.7 mN/m at 20 °C (68 °F)

## **10. STABILITY AND REACTIVITY INFORMATION**

**10.1 REACTIVITY:** No data available.

**10.2 CHEMICAL STABILITY:** Unstable ( ) Stable (X)

**10.3 POSSIBILITY OF HAZARDOUS REACTIONS:** Vapors may form explosive mixtures with air.

**HAZARDOUS POLYMERIZATION:** May occur ( ) Will not occur (X)

**10.4 CONDITIONS TO AVOID:** Heat, Sparks, Pilot Lights, Static Electricity, and Open Flame.



**10.5 INCOMPATIBLE MATERIALS:** Strong oxidants such as liquid chlorine, oxygen, sodium hypochlorite, inorganic acids e.g. nitric acid, perchloric acid and hydrogen peroxide. Acid chlorides, Acid anhydrides. Avoid aluminum and lead.

**10.6 HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes, Smoke, Carbon Monoxide, Aldehydes and other decomposition products where combustion is not complete.

## **11. TOXICOLOGICAL INFORMATION**

### **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:**

Routes of Entry: Inhalation--> x Skin--> x Ingestion--> x

#### **ACUTE HEALTH EFFECTS:**

Effects of overexposure:

Skin> Mildly irritating;

Inhalation> Irritation of the respiratory tract, Coughing, shortness of breath, dizziness and intoxication.

Ingestion> Essentially non-toxic. Causes mouth and throat irritation. Can cause nausea, dizziness, headache, and stupor.

Chronic: Repeated or prolonged exposure may irritate the mucous membranes in respiratory tract.

Medical Conditions Aggravated by Exposure> Skin contact may aggravate an existing dermatitis. May aggravate mucous membrane dysfunction. May adversely affect people with chronic eye conditions.

#### **ACUTE TOXICITY:**

The effects of overexposure shown in Section II are based on acute toxicity profiles. Typical values are:

Ingredient	Oral LD50 (Rat)	Skin LD50(Rabbit)	Inhalation LC50
Isobutanol	3350mg/kg (OECD Test Guideline 401)	2460mg/kg (OECD Test Guideline 402)	24.6mg/L/4hr

Additional Acute toxicity:

LD50 Intraperitoneal - mouse - 544 mg/kg  
LD50 Intravenous - mouse - 417 mg/kg  
LD50 Intraperitoneal - rabbit - 323 mg/kg  
LD50 Intraperitoneal - guinea pig - 1,201 mg/kg  
LD50 Intraperitoneal - Hamster - 1,401 mg/kg

**SKIN CORROSION/IRRITATION:** Skin - Rabbit Result: Irritating to skin. - 24 h

**SERIOUS EYE DAMAGE/EYE IRRITATION:** Eyes - Rabbit Result: Risk of serious damage to eyes. - 24 h (OECD Test Guideline 405)

**RESPIRATORY OR SKIN SENSITIZATION:** No data available

**MUTAGENIC EFFECTS:** Hamster fibroblast Result: negative  
(OECD Test Guideline 474) Mouse - male and female Result: negative

**CARCINOGEN STATUS:**

IARC - No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP – No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA – No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Carcinogenicity - rat - Oral**

**Tumorigenic:** Equivocal tumorigenic agent by RTECS criteria. Skin and

**Appendages:** Other: Tumors. Leukemia

**Carcinogenicity - rat - Subcutaneous**

**Tumorigenic:** Carcinogenic by RTECS criteria. Gastrointestinal: Tumors. Liver: Tumors.

**REPRODUCTIVE TOXICITY:** - Rat - male and female - inhalation (vapor) No significant adverse effects were reported

**Specific target organ toxicity (STOT-SE) - single exposure (Globally Harmonized System):** May cause respiratory irritation. - Respiratory Tract  
May cause drowsiness or dizziness. - Central nervous system

**Specific target organ toxicity (STOT-RE) - repeated exposure (Globally Harmonized System):** no data available

**Aspiration hazard:** No data available

**11.2 Additional Information:** Repeated dose toxicity Rat - male and female - inhalation (vapor) - NOAEL :  $\geq 7.5$  mg/l – (OECD Test Guideline 408)

Cough, Shortness of breath, Headache, Nausea, Vomiting, Central nervous system depression,  
RTECS: NP9625000

## 12. ECOLOGICAL INFORMATION

### 12.1 AQUATIC TOXICITY:

Toxicity to fish:

LC50 - Pimephales promelas (fathead minnow) - 1430 mg/l - 96 h

Flow through test

Toxicity to daphnia and other aquatic invertebrates:

EC50 - Daphnia pulex (Water flea) - 1,100 mg/l - 48 h

Static test

Toxicity to algae:

EC50 - Pseudokirchneriella subcapitata (green algae) - 1,799 mg/l - 72 h

Static test (OECD Test Guideline 201)

Toxicity to bacteria:

IC50 - Sludge Treatment - > 1,000 mg/l - 16 h

Growth inhibition

12.2 PERSISTENCE AND DEGRADABILITY: aerobic - Exposure time 28 d Result:  
70 - 80 % - Readily biodegradable (OECD Test Guideline 301D)

12.3 BIOACCUMULATIVE POTENTIAL: Log octanol/water partition coefficient of  
<3.0

This material is not expected to significantly bio-accumulate.

Bio-concentration Factor (BCF): No data available.

12.4 MOBILITY IN SOIL: No data available.

### 12.5 RESULTS OF PBT AND vPvB :

PBT assessment results: This substance is not classified as PBT or vPvB.

12.6 OTHER ADVERSE EFFECTS: No data available.

## 13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS: Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly it is the responsibility of the user to determine the proper storage, transportation, treatment and or disposal methodologies for spent materials and residues at time

of disposition. Dispose in accordance with all applicable disposal regulations. Incinerate under controlled conditions in a permitted facility.

**CONTAMINATED PACKAGING:** Dispose of as unused product

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

RCRA: The unused product is a RCRA hazardous waste if discarded. The RCRA ID number is: U140.

If the waste is a spent solvent, the appropriate spent solvent code should be used.

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 48 CFR 262

**14. TRANSPORT INFORMATION**

**Land Transport (DOT)**

- 14.1 USDOT ID Number-----> UN1212
- 14.2 USDOT Shipping Name-----> Isobutanol
- 14.3 USDOT Hazard Classification-----> 3 (Flammable Liquid)  
USDOT Label Codes-----> 3
- 14.4 USDOT Package Code-----> III
- 14.5 Marine Pollutant-----> No
- 14.6 Special precautions for user-----> None  
Emergency Response Guide-----> 129  
Reportable quantity-----> 5000lbs.

**Sea Transport (IMDG)**

- 14.1 ID Number-----> UN1212
- 14.2 Proper shipping name-----> ISOBUTANOL
- 14.3 Hazard Classification-----> 3 (Flammable Liquid)  
Label Codes-----> 3
- 14.4 Package Code-----> III
- 14.5 Marine Pollutant-----> No
- 14.6 Special precautions for user-----> Yes  
EMS-Number-----> F-E, S-D

**Air Transport (IATA)**

- 14.1 ID Number-----> UN1212
- 14.2 Proper shipping name-----> Isobutanol
- 14.3 Hazard Classification-----> 3 (Flammable Liquid)  
Label Codes-----> 3

14.4 Package Code-----> III  
14.5 Environmental hazard-----> None  
14.6 Special precautions for user-----> None

## **15. REGULATORY INFORMATION**

### **15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:**

#### **SARA TITLE III (Superfund Amendment and Reauthorization Act)**

SECTION 302 AND 304: Extremely Hazardous Substance List (40 CFR 355) - Not Listed  
SECTION 313: Toxic Chemicals Listing (40 CFR 372.65) - Not Listed  
SECTION 311/312: Hazard Categorization (40 CFR 370) - Acute Health Hazard and Fire Hazard

#### **CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)**

SECTION 102(A) Hazardous Substances (40 CFR 302.4) - Listed  
iso-Butanol CAS-No.78-83-1 Reportable Quantity - 5,000 pounds.  
SECTION 101(14) Reportable Quantity: 5,000 lbs

Listed on the following state Right to Know Hazardous Material Lists: CT, FL, IL, LA, MA, NJ, NY, PA, RI

Massachusetts Right to Know Components  
iso-Butanol CAS-No.78-83-1  
Pennsylvania Right to Know Components  
iso-Butanol CAS-No.78-83-1  
New Jersey Right to Know Components  
iso-Butanol CAS-No.78-83-1

California Prop. 65 Components  
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **TSCA (Toxic Substance Control Act)**

iso-Butanol CAS-No.78-83-1 is listed on the TSCA Inventory.

#### **International Inventories:**

<b><u>Country or Region</u></b>	<b><u>Inventory Name</u></b>	<b><u>On inventory yes/no</u></b>
---------------------------------	------------------------------	-----------------------------------

<b><u>Australia</u></b>	Australian Inventory of Chemical Substances (AICS)	Yes
-------------------------	--	-----

<u>Canada</u>	Domestic Substances List (DSL)	Yes
<u>Canada</u>	Non-Domestic Substances List (NDSL)	No
<u>China</u>	Inventory of Existing Chemical Substances in China (IECSC)	Yes
<u>Europe</u>	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
<u>Europe</u>	European List of Notified Chemical Substances (ELINCS)	No
<u>Japan</u>	Inventory of Existing and New Chemical Substances (ENCS)	Yes
<u>Japan</u>	Industrial Safety & Health Law Inventory (ISHL)	Yes
<u>Korea</u>	Existing Chemicals List (ECL)	Yes
<u>Mexico</u>	National Inventory of Chemical Substances (INSQ)	Yes
<u>New Zealand</u>	New Zealand Inventory	Yes
<u>Philippines</u>	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
<u>Switzerland</u>	Inventory of Notified New Substances (CHINV)	Yes
<u>Taiwan</u>	National Existing Chemical Inventory (NECI)	Yes
<u>United States &amp; Puerto Rico</u>	Toxic Substances Control Act Inventory	Yes

**15.2 CHEMICAL SAFETY ASSESSMENT: A chemical safety assessment has been carried out for this substance.**

## **16. OTHER INFORMATION:**

**HMIS** (Hazardous Materials Identification System)

**Hazard Rating:**

**4-Extreme**

**3-High**

**2-Moderate**

**1-Slight**

**0-Insignificant**

<b>NFPA RATINGS (SCALE 0-4):</b>	<b>Health=2</b>	<b>Fire=3</b>	<b>Reactivity=0</b>
<b>HMIS (SCALE 0-4):</b>	<b>Health=2</b>	<b>Fire=3</b>	<b>Reactivity=0 PPE=G</b>

**Hazard statement(s) from Section 2 and 3:**

**H226 Flammable liquid and vapor.**

**H315 Causes skin irritation.**

**H318 Causes serious eye damage.**

**H335 May cause respiratory irritation.**

**H336 May cause drowsiness or dizziness.**

**Date of preparation-----> July 14, 2004**

**Revision Number-----> 1.4**

**Revision Content-----> General update all sections**

**Revision Date-----> September 21, 2018**

**Prepared by-----> T.G. Fenstermaker, Jr.**

Acronyms:

ACGIH	-	American Conference of Governmental Industrial Hygienists
AIHA	-	American Industrial Hygiene Association
ANSI	-	American National Standards Institute
API	-	American Petroleum Institute
CERCLA	-	Comprehensive Emergency Response, Compensation, and Liability Act
DOT	-	U.S. Department of Transportation
EPA	-	U.S. Environmental Protection Agency
HMIS	-	Hazardous Materials Information System
IARC	-	International Agency For Research On Cancer
MSHA	-	Mine Safety and Health Administration
NFPA	-	National Fire Protection Association
NIOSH	-	National Institute of Occupational Safety and Health
NOIC	-	Notice of Intended Change (Proposed change to ACGIH TLV)
NTP	-	National Toxicology Program
OPA	-	Oil Pollution Act of 1990
OSHA	-	U.S. Occupational Safety & Health Administration
PEL	-	Permissible Exposure Limit (OSHA)
RCRA	-	Resource Conservation and Recovery Act
REL	-	Recommended Exposure Limit (NIOSH)
SARA	-	Superfund Amendments and Reauthorization Act of 1986 Title III
SCBA	-	Self-Contained Breathing Apparatus
STEL	-	Short-Term Exposure Limit (generally 15 minutes)
TLV	-	Threshold Limit Value
TSCA	-	Toxic Substances Control Act
TWA	-	Time Weighted Average (8hr.)
WHMIS	-	Canadian Workplace Hazardous Materials Information System

This information is furnished without warranty, representation, inducement of license of any kind, except that it is accurate to the best of G.J. Chemical's knowledge, or obtained from sources believed by G.J. Chemical Co., Inc. to be accurate, and G.J. Chemical Co., Inc. does not assume any legal responsibility for use or reliance upon same. Users are encouraged to conduct their own tests. Before using any product, read its label. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.