

G.J. CHEMICAL COMPANY, INC. SAFETY DATA SHEET

1. PRODUCT IDENTIFIER

1.1 PRODUCT NAME:-----> **WONDER SOLVE**

PRODUCT NUMBER(S):-----> 296900

TRADE NAMES/SYNONYMS: ----> Blend

RECOMMENDED USE: Solvent

USES ADVISED AGAINST: No information available

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Company: **G.J. CHEMICAL CO., INC.**

Address: **40 VERONICA AVENUE
SOMERSET, NJ 08873**

Telephone: **1-973-589-1450**

Fax: **1-973-589-3072**

1.4 Emergency Telephone Number

Emergency Phone: **1-800-424-9300 (CHEMTREC)**

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H225

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

2.2 GHS Label elements, including precautionary statements



Pictogram

GHS02

GHS05

GHS07

Signal word: **DANGER**

Hazard statement(s)

H226 Highly Flammable liquid and vapor.

H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness and dizziness.

Precautionary statement(s)

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS: None

3. INGREDIENTS

3.1 SUBSTANCE: Not applicable.

3.2 MIXTURE:

Ingredient	CAS No.	% by WT. Range	CLASSIFICATION
Cyclohexanone	108-94-1 EC-No.203-631-1 Index No.606-010-00-7 Reg.-No. 01-2119453616-35-XXXX	77.8	Flammable liquids (Category 3), H226 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332 Acute toxicity, Dermal (Category 4), H312 Skin irritation (Category 2), H315 Serious eye damage (Category 1), H318
2-Butanone	78-93-3 EC-No.201-159-0 Index-No.606-002-00-3 Reg.-No. 01-2119457290-43-XXXX	22.2	Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 STOT-SE (Category 3) Central Nervous System, H336

4. FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

INHALATION: WONDER SOLVE

****FIRST AID- Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep person warm and at rest. Treat symptomatically and supportively. Get medical attention immediately.**

SKIN CONTACT: WONDER SOLVE

****FIRST AID- Remove contaminated clothing and shoes**

immediately. Wash affected area with soap or mild detergent and large amounts of water until no evidence of chemical remains (approximately 15-20 minutes). Get medical attention immediately.

EYE CONTACT: WONDER SOLVE

****FIRST AID- Wash eyes immediately with large amounts of water or normal saline, occasionally lifting upper and lower lids, until no evidence of chemical remains (approximately 15-20 minutes). Remove contact lenses, if worn, after initial flush. Get medical attention immediately.**

INGESTION: WONDER SOLVE

****FIRST AID- Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Small amounts, which enter the mouth should be rinsed out until taste is gone. Get medical attention immediately.**

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Eye: Moderate to severe irritation; Vapors are mildly irritating to eyes.

Skin: Moderate irritant; Can be absorbed through skin.

Inhalation: Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma;

Ingestion: Moderately toxic, may irritate the mouth, throat and gastro-intestinal tract. Pulmonary aspiration hazard if swallowed and vomiting occurs.

Chronic: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Typical symptoms are cardiovascular disorders, sweetish taste in the mouth, nausea, vomiting, loss of appetite, strong thirst, burning of eyes and bleeding from the nose. Based on animal studies damage may occur to the kidney or liver.

Medical Conditions Aggravated by Exposure: Skin contact may aggravate an existing dermatitis. Inhalation may aggravate respiratory diseases e.g. Asthma. Other pre-existing medical conditions aggravated by exposure - disorders of the eye, liver, kidney & nervous system conditions (toxicosis, miscarriage) and infertility.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Specific details on antidote: No recommendation given.

5. FIRE FIGHTING MEASURES

Flash Point: -6.67°C (20°F) TCC

LEL %: 1.3 (V)

Auto-ignition Temp: N.D.

UEL %: 8.8 (V)

UNIFORM FIRE CODE: Flammable Liquid Class IB

5.1 SUITABLE EXTINGUISHING MEDIA: - Foam--> x CO2--> x Dry Chemical--> x Water-fog--> x Other--> Alcohol type aqueous film forming for large fires.

Unsuitable extinguishing media: Do not use waterjet.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: FIRE AND EXPLOSION HAZARD: DANGEROUS FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. VAPOR-AIR MIXTURES ARE EXPLOSIVE. Keep containers tightly closed. Extremely Flammable liquid; isolate from all sources of ignition. Closed containers may explode when exposed to extreme heat.

CONDITIONS OF FLAMMABILITY: Flammable in the presence of a source of ignition when the temperature is above the flash point.

HAZARDOUS COMBUSTION PRODUCTS: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, carbon oxides and other unidentified organic compounds evolve when this material undergoes combustion.

5.3 ADVICE FOR FIREFIGHTERS: Shut off source. Water fog may be used to cool closed containers to prevent pressure build up and possible auto ignition or explosion when exposed to extreme heat. Wear NIOSH/MSHA approved self-contained breathing apparatus (SCBA) for confined spaces and where there is exposure to vapors. Use full fire-fighting protective clothing. Keep unnecessary people away; isolate hazard area and deny entry. Avoid breathing vapors, stay upwind. Do not enter fire area without structural fire fighter's protective equipment including NIOSH/MSHA approved self-contained breathing apparatus (SCBA) in positive pressure mode. Use water spray to knock down vapors. Use halon, carbon dioxide extinguisher or dry powder for small fires. Large fires are best controlled by alcohol foam, fog, and water spray. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks. For massive fire in cargo area, use unmanned hose holder or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due

to fire. Isolate for 1/2 mile in all directions if tank, rail car or tank truck is involved in fire Extinguish only if fire can be stopped. Use flooding amounts of water as a fog; solid streams may be ineffective. Cool containers with flooding amounts of water from as far a distance as possible. Avoid breathing vapors; keep upwind. If fire is uncontrollable or containers are exposed to direct flame, water may be ineffective. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures.

6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Extremely Flammable; Eliminate ignition sources in the vicinity of the spill or released vapor. Immediately evacuate all nonessential people. Verify that responders are properly trained and wearing appropriate respiratory equipment and fire resistant protective clothing during cleanup operations. For large spills evacuate downwind areas as conditions warrant to prevent exposure and to allow vapors or fumes to dissipate.

6.2 ENVIRONMENTAL PRECAUTIONS:

Keep out of water sources, drains and sewers. Do not flush into surface water or sanitary sewer system.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Methods for cleanup and containment:

Use explosion proof equipment. Shut off valves, contain spill, keep out of water sources and sewers, for smaller spills add non-flammable absorbent in spill area.

For large spills use foam on spill to minimize vapors clean up by vacuuming then using non-flammable absorbent.

Methods for disposal:

Place all saturated absorbent, using non-sparking tools, in an approved container for disposal. Minimize breathing vapors and skin contact, ventilate confined areas, open all windows and doors, assure conformity with applicable government regulations.

REPORTABLE QUANTITY (RQ): Cyclohexanone, 2-Butanone and Blend – 5000lbs.

The Superfund Amendments and Reauthorization Act (SARA) Section 304 requires that a release equal to or greater than the reportable quantity for this substance be immediately reported to the local emergency planning committee and the state emergency response commission (40 CFR 355.40). If the release of this substance is reportable under CERCLA Section 103, the national response center must be notified immediately at (800) 424-8882 or (202) 426-2675 in the metropolitan Washington, D. C. area (40 CFR 302.6).

6.4 REFERENCE TO OTHER SECTIONS: See Sections 8 and 13.

7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING: This material presents a fire hazard. Liquid quickly evaporates and forms vapor (fumes), which can catch fire and burn with explosive violence. Invisible vapor spreads easily and can be set on fire by many sources, such as pilot lights, welding equipment, and electrical motors and switches. Vapor is heavier than air and can travel considerable distance to a source of ignition and flash back. Avoid breathing vapors in top of shipping container. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid work practices that may release volatile components in the atmosphere. Avoid contaminating soil or releasing material into sewage and drainage systems. Use non-sparking tools to open or close containers.

Advice on general occupational hygiene:

Wash hands before breaks and after work. Keep away from food, drink and animal feeding stuffs. When using do not smoke.

STATIC HAZARD > Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not be sufficient. For more information refer to OSHA Standard 29CFR 1910.106 “Flammable and Combustible Liquids” and National Fire Protection Association (NFPA 77) “Recommended Practice on Static Electricity”.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Follow maximum allowed pile heights specified in the BOCA codes or the NFPA manual. Local fire authorities should be notified for storage of this material in any quantity. Local permits are required for storage in warehouse quantities. Recommended storage temperature: 15 - 25°C. Store large quantities only in cool, dry areas in buildings designed to comply with OSHA 1910.106. Keep containers tight and upright to prevent leakage. Do not contact with oxidizing materials. Keep containers closed when not in use. Do not take internally. Hygroscopic. Storage class (TRGS 510): 3: Flammable liquids

CONTAINER WARNINGS > Containers should be Bonded and Grounded when pouring. Avoid free fall of liquid in excess of a few inches. Empty containers release residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, or expose such containers to heat, sparks, static electricity or other sources of ignition. Do not attempt to clean. "Empty" drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner.

7.3 SPECIFIC END USES: Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROL (PERSONAL PROTECTION)

8.1 CONTROL PARAMETERS:

Ingredient	CAS No.	% by WT. Range	Exposure Limits
Cyclohexanone	108-94-1 EC-No.203-631-1 Index No.606-010-00-7 Reg.-No. 01-2119453616-35-XXXX	77.8	50ppm TWA (OSHA) 20ppm TWA (ACGIH) 50ppm STEL (ACGIH) 25ppm TWA (NIOSH) 700ppm IDLH
2-Butanone	78-93-3 EC-No.201-159-0 Index-No.606-002-00-3 Reg.-No. 01-2119457290-43-XXXX	22.2	200ppm TWA (ACGIH) 300ppm STEL (ACGIH) 200ppm TWA (OSHA) 300ppm STEL (OSHA) 200ppm TWA (NIOSH) 300ppm STEL (NIOSH) 3000ppm IDLH

Key: (PEL) = Permissible Exposure Limit OSHA
(TLV) = Threshold Limit Value OSHA & ACGIH
(STEL) = Short Term Exposure Limit ACGIH
(WEEL) = USA. Workplace Environmental Exposure Levels
(TWA) = Time Weighted Average
CAS = Chemical Abstracts Registry Number
IDLH = Immediate Danger to Life and Health
N.E. =None Established

8.2 EXPOSURE CONTROLS

EXPOSURE GUIDELINES: Consider the potential hazards of this material (Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended.

ENGINEERING CONTROLS: Provide general dilution or local exhaust ventilation in volume and pattern to keep concentrations within permitted exposure limits. All areas should be ventilated in accordance with OSHA Regulation 29 CFR Part 1910. Explosion proof motors should be used in mechanical ventilation.

RESPIRATORY PROTECTION: The specific respirator selected must be based on contamination levels found in the work place, must not exceed the working limits of the respirator and be jointly approved by the National Institute for Occupational Safety and Health and the Mine Safety and Health Administration (NIOSH-MSHA):

For known vapor concentrations use a NIOSH/MSHA air purifying respirator with full face-piece and organic vapor cartridge for exposures >1 <10 times ACGIH TWA. For exposures greater than 10 times ACGIH TWA or for unknown vapor concentrations use positive pressure self contained breathing apparatus with full face-piece.

BODY CLOTHING: Use chemical resistant apron or other impervious clothing. Remove and wash contaminated clothing before reuse. Users should determine acceptable performance characteristics of protective clothing.

SKIN PROTECTION: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

Full contact:

Glove material: butyl-rubber

Glove thickness: 0.3 mm

Break through time: 292 min

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: >480 min

HYGIENE: Use good personal hygiene practices, wash hands before eating, drinking, smoking or using toilet facilities.

EYE /FACE PROTECTION: Use safety eyewear with splash-guards or face shield. Shower and eyewash should be located in an easily accessible location to the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Wonder Solve Blend

APPEARANCE:

Clear Liquid

COLOR:

Colorless to pale yellow

ODOR:

Peppermint –like odor

ODOR THRESHOLD:

No Data Available

pH:

No Data Available

MOLECULAR WEIGHT:

No data available

MELTING POINT:

No data available

BOILING POINT:

175-312 °F

SPECIFIC GRAVITY:

0.912@20°C

VAPOR PRESSURE:

18.7mm Hg @ 20°C (68.0°F)

VAPOR DENSITY:

3.2

WATER SOLUBILITY:

9.8%@20°C

PARTITION COEFFICIENT N-OCTANOL/WATER	No data available
FLASH POINT:	-6.67°C (20°F) - closed cup
EVAPORATION RATE (BUTYL ACETATE=1):	1.23
UPPER FLAMMABILITY LIMIT:	8.8% (V)
LOWER FLAMMABILITY LIMIT:	1.3% (V)
AUTO IGNITION TEMPERATURE:	No data available
DECOMPOSITION TEMPERATURE:	No Data Available
VISCOSITY:	No Data Available
EXPLOSIVE PROPERTIES:	No Data Available
OXIDIZING PROPERTIES:	No Data Available
OTHER INFORMATION:	No Data Available

10. STABILITY AND REACTIVITY INFORMATION

10.1 REACTIVITY: No data available.

10.2 CHEMICAL STABILITY: Unstable () Stable (X)
Stable under normal temperatures and pressures.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS: Vapors may form explosive mixtures with air.

HAZARDOUS POLYMERIZATION--> May occur () Will not occur(X)

10.4 CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight. Exposure to moisture.

10.5 INCOMPATIBLE MATERIALS: Strong oxidants such as caustic soda, liquid chlorine, oxygen, sodium hypochlorite, inorganic acids e.g. hydrochloric acid hydrogen peroxide. Copper or copper alloys. ACETALDEHYDE: Violent condensation reaction NITRIC ACID + HYDROGEN PEROXIDE: Formation of explosive product PERCHLORIC ACID: Violent decomposition

10.6 HAZARDOUS DECOMPOSITION PRODUCTS: Fumes, Smoke, Carbon Monoxide, Aldehydes and other decomposition products where combustion is not complete.

11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

Routes of Entry: Inhalation--> x Skin--> x Ingestion--> x Eye--> x

ACUTE HEALTH EFFECTS:

Effects of overexposure:

Eye> Moderate to severe irritation; Vapors are mildly irritating to eyes.

Skin> Moderate irritant; Can be absorbed through skin.

Inhalation> Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma;

Ingestion> Moderately toxic, may irritate the mouth, throat and gastro-intestinal tract. Pulmonary aspiration hazard if swallowed and vomiting occurs.

Chronic: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Typical symptoms are cardiovascular disorders, sweetish taste in the mouth, nausea, vomiting, loss of appetite, strong thirst, burning of eyes and bleeding from the nose. Based on animal studies damage may occur to the kidney or liver.

Medical Conditions Aggravated by Exposure> Skin contact may aggravate an existing dermatitis. Inhalation may aggravate respiratory diseases e.g. Asthma. Other pre-existing medical conditions aggravated by exposure - disorders of the eye, liver, kidney & nervous system conditions (toxicosis, miscarriage) and infertility.

Medical Conditions Aggravated by Exposure> Skin contact may aggravate an existing dermatitis.

ACUTE TOXICITY:

The effects of overexposure shown in Section III are based on acute toxicity profiles. Typical values are:

Ingredient	 Oral LD50 (Rat)	 Skin LD50 (Rabbit)	 Inhalation LC50	
Cyclohexanone	1.5-2.65g/kg	>.794->3g/kg	6.2mg/L/4hr	
2-Butanone	2737g/kg	6480mg/kg	32000mg/m3/4h	

Cyclohexanone –

SKIN CORROSION/IRRITATION: Skin - Rabbit Result: Irritating to skin.

SERIOUS EYE DAMAGE/EYE IRRITATION: Eyes - Rabbit Result: Risk of serious damage to eyes. - 24 h

RESPIRATORY OR SKIN SENSITIZATION:

Test Type: Maximization test Species: guinea pig

Method: In vivo

Result: Did not cause sensitization on laboratory animals.

MUTAGENIC EFFECTS: Not mutagenic in Ames Test.

Ames test: S. typhimurium; Result: negative

Human fibroblast; Result: Laboratory experiments have shown mutagenic effects.

CARCINOGEN STATUS:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

REPRODUCTIVE TOXICITY: Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity (STOT-SE) - single exposure (Globally Harmonized System): No Data Available; Acute inhalation toxicity - Breathing difficulties

Specific target organ toxicity (STOT-RE) - repeated exposure (Globally Harmonized System): No Data Available.

11.2 ADDITIONAL DATA: No Data Available

2-Butanone -

SKIN CORROSION/IRRITATION: Skin - Rabbit Result: No skin irritation (OECD Test Guideline 404)

SERIOUS EYE DAMAGE/EYE IRRITATION: Eyes - Rabbit Result: Irritating to eyes. (OECD Test Guideline 405)

RESPIRATORY OR SKIN SENSITIZATION: No data available

MUTAGENIC EFFECTS: Methyl Ethyl Ketone has shown to be without genotoxic activity in a variety of in vitro and in vivo tests.

CARCINOGEN STATUS:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Specific target organ toxicity (STOT-SE) - single exposure (Globally Harmonized System) May cause drowsiness or dizziness.

Specific target organ toxicity (STOT-RE) - repeated exposure (Globally Harmonized System) no data available

REPRODUCTIVE TOXICITY: Methyl ethyl Ketone is concluded not to be a developmental toxicant.

11.2 ADDITIONAL DATA: Central nervous system depression, Gastrointestinal disturbance, narcosis.

MEK is not neurotoxic. It has been shown to potentiate the neurotoxic effects of hexane, 2, 5 hexanedione, and methyl-n-butyl ketone. Methyl Ethyl Ketone has also potentiated the liver toxicity of halogenated solvents in animal studies.

12. ECOLOGICAL INFORMATION

DANGEROUS TO AQUATIC LIFE IN HIGH CONCENTRATIONS

May be dangerous if it enters water intakes.

Notify local health and pollution control officials.

Notify operators of nearby water intakes.

Cyclohexanone -

DANGEROUS TO AQUATIC LIFE IN HIGH CONCENTRATIONS

May be dangerous if it enters water intakes.

Notify local health and pollution control officials.

Notify operators of nearby water intakes.

12.1 AQUATIC TOXICITY (Acute):

Toxicity to Fish;

LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l - 96 h

Test Type: flow-through test

Daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 820 mg/l - 24 h

Method: OECD Test Guideline 202

Toxicity to Algae:

EC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 100 mg/l

72 h - static test. Method: OECD Test Guideline 201

Toxicity to Bacteria:

EC 50 (activated sludge): > 1,000 mg/l – 30 min. – static test

Method: OECD Test Guideline 209

12.2 PERSISTANCE AND DEGRADABILITY:

Biodegradability Result: 90 - 100 % - Readily biodegradable

12.3 BIOACCUMULATIVE POTENTIAL: The partition coefficient of n-octanol/water is log Pow 0.81

BIOCONCENTRATION FACTOR (BCF): <100

When released into the air, this material is expected to have a half-life between 1 and 10 days.

12.4 SOIL MOBILITY: When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to quickly evaporate.

12.5 RESULTS OF PBT AND vPvB:

PBT assessment results: This substance is not classified as PBT or vPvB.

12.6 OTHER ADVERSE EFFECTS: No data available.

2-Butanone -

12.1 AQUATIC TOXICITY:

Toxicity to fish:

NOEC - Cyprinodon variegatus (sheepshead minnow) - 400 mg/l - 96 h mortality

LC50 - Pimephales promelas (fathead minnow) - 3,130 - 3,320 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

LC50 - Daphnia magna (Water flea) - > 520 mg/l - 48 h

EC50 - Daphnia magna (Water flea) - 7,060 mg/l - 24 h

At above 100ppm it may inhibit the growth of blue-green algae. Such concentrations are unlikely except for short periods following accidental spillage.

12.2 PERSISTANCE AND DEGRADABILITY: Extensive data demonstrate that Methyl ethyl Ketone is readily biodegradable. Studies in activated sludge showed that Methyl Ethyl Ketone is easily degraded and is not toxic to sludge microrganisms in concentrations up to 800microgm./L.

Photodegradation half-life for Methyl Ethyl ketone is 9.8 hours.

12.3 BIOACCUMULATIVE POTENTIAL: No direct information on Methyl Ethyl Ketone is available on accumulation in biological material. The high water solubility, rapid degradation by aquatic bacteria, and low octanol/water partition coefficient of log Pow = 0.29 suggest that it is unlikely to concentrate in aquatic species.

12.4 MOBILITY IN SOIL: No data available

12.5 RESULTS OF PBT AND vPvB :

PBT assessment results: This substance is not classified as PBT or vPvB.

12.6 OTHER ADVERSE EFFECTS: No data available

13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS: Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly it is the responsibility of the user to determine the proper storage, transportation, treatment, and or disposal methodologies for spent materials and residues at time of disposition. Dispose in accordance with all applicable disposal regulations. Incinerate under controlled conditions in a permitted facility.

CONTAMINATED PACKAGING: Dispose of as unused product.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

RCRA: The unused product is a RCRA hazardous waste if discarded. The RCRA ID number is: Cyclohexanone - U057 and D001; 2-Butanone – U159 and D001. If the waste is a spent solvent, the appropriate spent solvent code should be used.

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 48 CFR 262

14. TRANSPORT INFORMATION

Land Transport (DOT)

14.1 USDOT ID Number-----> UN1993

14.2 USDOT Shipping Name-----> Flammable Liquid, n.o.s.

14.3 USDOT Hazard Classification-----> 3 (Flammable Liquid)

USDOT Label Codes-----> 3

14.4 USDOT Package Code-----> III

14.5 Marine Pollutant-----> No

14.6 Special precautions for user-----> No
Emergency Response Guide-----> 128
Reportable quantity-----> 5000lbs. - Blend

Sea Transport (IMDG)

14.1 ID Number-----> UN1993
14.2 Proper shipping name-----> FLAMMABLE LIQUID, N.O.S.
14.3 Hazard Classification-----> 3 (Flammable Liquid)
Label Codes-----> 3
14.4 Package Code-----> III
14.5 Marine Pollutant-----> No
14.6 Special precautions for user-----> No
EMS-Number-----> F-E, S-D

Air Transport (IATA)

14.1 ID Number-----> UN1993
14.2 Proper shipping name-----> Flammable Liquid, n.o.s.
14.3 Hazard Classification-----> 3 (Flammable Liquid)
Label Codes-----> 3
14.4 Package Code-----> III
14.5 Environmental hazard-----> No
14.6 Special precautions for user-----> None

15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

SARA TITLE III (Superfund Amendment and Reauthorization Act)

SECTION 302 AND 304: Extremely Hazardous Substance List (40 CFR 355) - Not Listed

SECTION 313: Toxic Chemicals Listing (40 CFR 372.65) - Not Listed

SECTION 311/312: Hazard Categorization (40 CFR 370) - Acute Health Hazard, Chronic Health Hazard, Fire Hazard.

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

SECTION 102(A) Hazardous Substances (40 CFR 302.4)- Listed

Cyclohexanone CAS-No.108-94-1 and Ethyl methyl ketone CAS-No. 78-93-3

Reportable Quantity - 5,000 pounds.

SECTION 101(14) Cyclohexanone CAS-No.108-94-1, Ethyl methyl ketone CAS-No. 78-93-3 and Blend; Reportable Quantity: 5,000 lbs

Massachusetts Right to Know Components
Cyclohexanone CAS-No.108-94-1
Ethyl methyl ketone CAS-No. 78-93-3

Pennsylvania Right to Know Components
Cyclohexanone CAS-No.108-94-1
Ethyl methyl ketone CAS-No. 78-93-3

New Jersey Right to Know Components
Cyclohexanone CAS-No.108-94-1
Ethyl methyl ketone CAS-No. 78-93-3

California Prop. 65 Components
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

TSCA (Toxic Substance Control Act)
Cyclohexanone CAS-No.108-94-1 and Ethyl methyl ketone CAS-No. 78-93-3 are listed on the TSCA Inventory.

15.2 CHEMICAL SAFETY ASSESSMENT: A chemical safety assessment has not been carried out for this mixture.

16. OTHER INFORMATION:

Hazard Rating:

- 4-Extreme
- 3-High
- 2-Moderate
- 1-Slight
- 0-Insignificant

NFPA RATINGS (SCALE 0-4): Health=2 Fire=3 Reactivity=0
HMIS RATINGS (SCALE 0-4): Health=2 Fire=3 Reactivity=0 PPE=

Hazard statement(s) from Section 2 and 3:
H226 Highly Flammable liquid and vapor.
H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness and dizziness.

Date of preparation-----> June 11, 1997
Revision Number-----> 1.6
Revision Content-----> General update all sections
Revision Date-----> December 18,2018
Prepared by-----> T.G. Fenstermaker, Jr.

Acronyms:

ACGIH - American Conference of Governmental Industrial Hygienists
AIHA - American Industrial Hygiene Association

ANSI	-	American Nation Standards Institute
API	-	American Petroleum Institute
CERCLA	-	Comprehensive Emergency Response, Compensation, and Liability Act
DOT	-	U.S. Department of Transportation
EC-50	-	Effective Concentration
EPA	-	U.S. Environmental Protection Agency
HMIS	-	Hazardous Materials Information System
IARC	-	International Agency For Research On Cancer
LD-50	-	Lethal Dose
MAK	-	Germany Maximum Concentration Values
MSHA	-	Mine Safety and Health Administration
NFPA	-	National Fire Protection Association
NIOSH	-	National Institute of Occupational Safety and Health
NOIC	-	Notice of Intended Change (Proposed change to ACGIH TLV)
NTP	-	National Toxicology Program
OPA	-	Oil Pollution Act of 1990
OSHA	-	U.S. Occupational Safety & Health Administration
PEL	-	Permissible Exposure Limit (OSHA)
RCRA	-	Resource Conservation and Recovery Act
REL	-	Recommended Exposure Limit (NIOSH)
SARA	-	Superfund Amendments and Reauthorization Act of 1986 Title III
SCBA	-	Self-Contained Breathing Apparatus
STEL	-	Short-Term Exposure Limit (generally 15 minutes)
TLV	-	Threshold Limit Value
TSCA	-	Toxic Substances Control Act
TWA	-	Time Weighted Average (8hr.)
WHMIS	-	Canadian Workplace Hazardous Materials Information System

This information is furnished without warranty, representation, inducement of license of any kind, except that it is accurate to the best of G.J. Chemical's knowledge, or obtained from sources believed by G.J. Chemical Co., Inc. to be accurate, and G.J. Chemical Co., Inc. does not assume any legal responsibility for use or reliance upon same. Users are encouraged to conduct their own tests. Before using any product, read its label. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.