

# QUALITY CONTROL DEPARTMENT

ORDER NUMBER

## SPECIFICATION SHEET



### PRODUCT

HydroxyethylAcrylate400-650ppm

178811 -0100

### SPECIFICATION

04211/OMN/GJ

### SPECIFICATION VERSION

1.1000

### SPECIFICATION DATE

01/01/2007

### PRODUCT SPECIFICATION

TEST	TEST ID	UNITS	REQUIREMENTS
Date Heading	Date Heading		Use By Date, Expiration Date, Retest Date, None
Appearance (c)	L-460		Clear
Gas Chromatograph (n)	L-155	% wt.	97 =< Value =< 100 % wt.
Color (n)	L-020	APHA	0 =< Value =< 30 APHA
Specific Gravity 20C (n)	L-005		1.108 =< Value =< 1.11
Water in volatile solvents (n)	L-036	%	0 =< Value =< .25 %
Acidity (as Acrylic Acid) (n)	L-053	% wt.	0 =< Value =< 1 % wt.
MEHQ Acrylates (n)	L-150	ppm	400 =< Value =< 650 ppm
Refractive Index 20C (n)	L-001	(n)	1.445 =< Value =< 1.455 (n)
Country Of Origin	COUNTRY		
Manufacture Name	MFG NAME		
Shelf Life	SHELF LIFE		

### REMARKS

### DOT MARKINGS

UN CODE	PACKAGING GROUP	CAS NUMBER
2922	III	818-61-1

### DOT NAME

Corrosive Liquid, Toxic, N.O.S., Stabalized(Hydroxyethyl acrylate, stabilized)

### CONTAINS

### HAZARD TEXT

Important

The information on the sheet is believed to be accurate but is not warranted to be so. Protective equipment, health effects, and other related safety measures are based on intended and anticipated product use. Recipients are advised to confirm in advance of need that the information is applicable and suitable to their circumstances.