

QUALITY CONTROL DEPARTMENT

ORDER NUMBER

SPECIFICATION SHEET



PRODUCT
Naphtha 2429 (VM&P) 210500 -0020

SPECIFICATION	SPECIFICATION VERSION	SPECIFICATION DATE
11115/GJ/CIT	1.5000	01/01/2006

PRODUCT SPECIFICATION			
TEST	TEST ID	UNITS	REQUIREMENTS
Date Heading	Date Heading		Use By Date, Expiration Date, Retest Date, None
Appearance (c)	L-460		Clear
Assay Gas Chromatography (n)	L-099		Conforms
Color~ Saybolt (n)	L-020-1	Saybolt	28 =< Value =< 30 Saybolt
Water in volatile solvents (n)	L-036	%	0 =< Value =< .04 %
Specific Gravity 15.6C (n)	L-010		.715 =< Value =< .76
Aniline Point (c)	L-052		150 F max
Copper Corrosion (c)	L-470		1.2 max
Sulfur(Trace)in Hydrocarbons c	L-467		50 ppm max
IBP Distillation Range (c)	L-455-1	deg C	113 =< Value =< 154 deg C
DP Distillation Range (c)	L-455-2	deg C	0 =< Value =< 154 deg C
Flash Point (c)	L-024		50 F min
Aromatic Content by G.C. (n)	L-065	% wt.	0 =< Value =< 2 % wt.
Refractive Index 20C (n)	L-001	(n)	1.409 =< Value =< 1.42 (n)
Country Of Origin	COUNTRY		
Manufacture Name	MFG NAME		
Shelf Life	SHELF LIFE		

REMARKS

DOT MARKINGS

UN CODE	PACKAGING GROUP	CAS NUMBER
1268	II	64742-49-0

DOT NAME
UN1268, Petroleum Distillates, n.o.s. (Naphtha Solvent) 3, PGI

CONTAINS

HAZARD TEXT

QUALITY CONTROL DEPARTMENT

ORDER NUMBER

SPECIFICATION SHEET



Important

The information on the sheet is believed to be accurate but is not warranted to be so. Protective equipment, health effects, and other related safety measures are based on intended and anticipated product use. Recipients are advised to confirm in advance of need that the information is applicable and suitable to their circumstances.