

QUALITY CONTROL DEPARTMENT

ORDER NUMBER

SPECIFICATION SHEET



PRODUCT	
Petroleum Ether 35-60C	221900 -0100

SPECIFICATION	SPECIFICATION VERSION	SPECIFICATION DATE
06670/GJ/SHR	1.1000	02/20/2017

PRODUCT SPECIFICATION			
TEST	TEST ID	UNITS	REQUIREMENTS
Date Heading	Date Heading		Use By Date
IBP Distillation Range (c)	L-455-1	deg C	95 =< Value =< 100 deg C
DP Distillation Range (c)	L-455-2	deg C	129 =< Value =< 140 deg C
API Gravity 15.6C (n)	L-011		88.6 =< Value =< 90.8
Specific Gravity 15.6C (n)	L-010		.6365 =< Value =< .6429
Pounds per Gallon 15.6C (n)	L-007-3	lbs/gal.	5.297 =< Value =< 5.351 lbs/gal.
Copper Corrosion (c)	L-470		1A minimum
Color~ Saybolt (n)	L-020-1	Saybolt	>= 30 Saybolt MINIMUM
Nonvolatile Matter (n)	L-440-4	mg/100ml	0 =< Value =< 1 mg/100ml
Benzene by GC-MS	L-651		2ppm max.
Acidity as Acetic acid (c)	L-055-8		Pass

REMARKS

DOT MARKINGS

UN CODE	PACKAGING GROUP	CAS NUMBER
1268	II	8032-32-4

DOT NAME
Petroleum Distillates, n.o.s. (Pentanes, Hexanes)

CONTAINS

HAZARD TEXT

Important

The information on the sheet is believed to be accurate but is not warranted to be so. Protective equipment, health effects, and other related safety measures are based on intended and anticipated product use. Recipients are advised to confirm in advance of need that the information is applicable and suitable to their circumstances.